





Systems - Lines | 72 topLED 22 W DC 24 V | CRI 90  
83944W00



Technical data	
Type	Cabled - -
Installation position	Cable
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward
Nominal power	22 W DC
Source lumens	2080 lm
Input voltage range	24V
Frequency	50-60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V - PUSH DIM
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	0.365 Kg
Electrostatic discharge protection	No
Surge protection	No




### Finishing casing

Material	Aluminium
Processing	Coating

### Finishing diffuser

Material	PC
Colour	opaline

### Electronics

	81416 On/Off Driver 220~240V AC 120 W (1 - 5 art.)
	81417 On/Off Driver 220~240V AC 180 W (1 - 8 art.)
	83042 1-10V - Push and Simply Dim - DALI-2 Controller (1 - 13 art.)



Systems - Lines | 72 topLED 22 W DC 24 V | CRI 90 | Base  
**83944W00**


Single emission systems or lines for indoor application. The warm white LED light source with a diffused light distribution is composed of 72 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2080 lm, with a 94.5 lm/W nominal luminous efficacy.

The device body is made of aluminium, processed by means of coating; the diffuser is made of PC. The ingress protection degree is IP40; the total weight is of 0.365 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 22 W.

The device features protection class III and can be cable-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



### Energy efficiency class

This product contains 2 light sources of energy efficiency class F.

### Illuminotechnical Features

Light Output Ratio (LOR)	64 %
Source lumens	2080 lm
Delivered lumens	1351 lm
Consumption	22 W
Luminaire efficacy	61 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80

Standard Operating Ambient Temperature -20 / +50°C

### LED Life / Failure Ratio

L70 B20 C0 72500h (at Tj 115 Ta 25 )

### UGR

UGR axial	22.4
UGR transversal	25.4
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C90/C270 optics	116°
C0/C180 optics	180°
Light distribution symmetry	Symmetrical 2 axis



Ink system\_L | Lines | Accessories  
**83944W00**

		<p>Cable cover            Material:PC, processing:Coating.</p>	<p><b>Code</b>  <u>81424</u></p>
		<p>Junction            Type linear.            Material:PC, processing:Coating.</p>	<p><b>Code</b>  <u>81418</u></p>
		<p>Junction - Electrified black L connector            Type linear.            Material:PC, processing:Coating.</p>	<p><b>Code</b>  <u>81419</u></p>
		<p>Junction            Type linear.            Material:PC, processing:Coating.</p>	<p><b>Code</b>  <u>81420</u></p>
		<p>Closing cap - Electrified black closing plug            Material:PC, processing:Coating.</p>	<p><b>Code</b>  <u>81421</u></p>
		<p>Profile            Material:Aluminium, processing:Coating.</p>	<p><b>Code</b>  <u>84010</u></p>
		<p>Profile            Material:Aluminium, processing:Coating.</p>	<p><b>Code</b>  <u>84011</u></p>
		<p>Bracket - 2X            installation position: wall lights, ceiling.            Material:Aluminium, processing:Coating.</p>	<p><b>Finish</b>  <b>Code</b>  <u>84017</u></p>




Ink system\_L | Lines | Accessories  
**83944W00**



Cable cover - 2X  
 Material:Iron, processing:Coating.

**Code**  
81422




Cable cover - 2X  
 Material:Rubber, colour:black.

**Code**  
81423



Cables for suspension  
 Material:Aluminium, processing:Coating.

**Code**  
81425




Template

**Code**  
83186



Tool


**Code**  
81427




Cables for suspension  
 Material:Aluminium, processing:Coating.

**Code**  
83426

Track  
 Length: 1000mm.  
 Material:Aluminium, processing:Coating.

**Finish**  
 **Code**  
83432

Track  
 Length: 2000mm.  
 Material:Aluminium, processing:Coating.

**Finish**  
 **Code**  
83434



Ink system\_L | Lines | Accessories  
**83944W00**

Junction  
Material:Aluminium, processing:Coating.

**Finish**  
█ **Code**  
83436

Junction  
Material:Aluminium, processing:Coating.

**Finish**  
█ **Code**  
83438

Junction  
Material:Aluminium, processing:Coating.

**Finish**  
█ **Code**  
83440

Junction

**Code**  
83442

Cables for suspension  
Material:Aluminium, processing:Coating.

**Code**  
83443

Cable  
Length 1000 mm; colors: black.

**Code**  
83445

Cable  
Length 1000 mm; colors: black.

**Code**  
83446



Profile - Kit 2 x  
Material:Aluminium, colour:5G 9005 Black, processing:Coating.

**Code**  
81430



Ink system\_L | Lines | Accessories  
**83944W00**

		<p>Profile - Kit 5 x          Material:Aluminium, colour:5G 9005 Black, processing:Coating.</p>	<p><b>Code</b>  <u>81426</u></p>
		<p>Cable          Type of cable power cable; Length 1000 mm; insulation double; section 1.5 mm<sup>2</sup>; cable gland: no; colors: black - red.</p>	<p><b>Code</b>  <u>84016</u></p>
		<p>Cable          Type of cable power cable; Length 10000 mm; insulation double; section 1.5 mm<sup>2</sup>; cable gland: no; colors: black - red.</p>	<p><b>Code</b>  <u>81411</u></p>
		<p>Cable          Type of cable power cable; Length 5000 mm; insulation double; section 1.5 mm<sup>2</sup>; cable gland: no; colors: black - red.</p>	<p><b>Code</b>  <u>81410</u></p>