


#### Systems - Lines | topLED 0 W DC 24 V | CRI 90 83990W00



Technical data	
Designer	Linea Light
Construction year	2020
Туре	Cabled
Installation position	Cable
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward
Nominal power	0 W DC
Input voltage range	24 V
Frequency	50-60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes

Technical data	
Designer	Linea Light
Construction year	2020
Туре	Cabled
Installation position	Cable
Installation environment	Indoor
Light Source LED	
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward
Nominal power	0 W DC
Input voltage range	24 V
Frequency	50-60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
C.V C.C. Converter	Converter 24V included
Dimmable article	DALI-2 - P2P
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	Yes
Type of light emission	Single emission





Finishing casing			
Material	PU		
Colour	white		
Finishing mou	inting frame		
Finishing mou	Inting frame PC		

Coating

Processing

0.867 Kg

No

Net weight

Surge protection

Electrostatic discharge protection



Ink system\_L | Lines | Accessories 83990W00

071 24 TM 18 19	Junction Type linear. Material:PC, processing:Coating.	<b>Code</b> 81418
24   048   18	Junction - Electrified black L connector Type linear. Material:PC, processing:Coating.	<b>Code</b> 81419
48 24 71	Junction Type linear. Material:PC, processing:Coating.	<b>Code</b> 81420
	Junction Material:Aluminium, processing:Coating.	Finish Code 83436
	Junction	<b>Code</b> 83442
	Junction Material:Aluminium, processing:Coating.	Finish Code 83438
	Junction	Finish Code





Cable

Type of cable power cable; Length 5000 mm; insulation double; section 1.5 mm²; cable gland: no; colors: black - red.

Code

83440

81410

Material: Aluminium, processing: Coating.



## Ink system\_L | Lines | Accessories 83990W00

6	11 (see 25) 18 10000	Cable Type of cable power cable; Length 10000 mm; insulation double; section 1.5 mm²; cable gland: no; colors: black - red.	<b>Code</b> 81411
6	11 (188 m) 1000	Cable Type of cable power cable; Length 1000 mm; insulation double; section 1.5 mm²; cable gland: no; colors: black - red.	<b>Code</b> 84016
		Cable Length 1000 mm; colors: black.	<b>Code</b> 83445
		Cable Length 1000 mm; colors: black.	<b>Code</b> 83446
	max 2000 13 35	Cables for suspension Material:Aluminium, processing:Coating.	<b>Code</b> 81425
	max 2000   19   19   10   23	Cables for suspension Material:Aluminium, processing:Coating.	<b>Code</b> 83426
		Cables for suspension Material:Aluminium, processing:Coating.	<b>Code</b> 83443
	8 12 1000	Profile - Kit 5 x Material:Aluminium, colour:5G 9005 Black, processing:Coating.	<b>Code</b> 81426



## Ink system\_L | Lines | Accessories 83990W00

1	8 12 1000	Profile - Kit 2 x Material:Aluminium, colour:5G 9005 Black, processing:Coating.	<b>Code</b> 81430
1/=	25 P	Profile Material:Aluminium, processing:Coating.	<b>Code</b> 84010
	25 P	Profile Material:Aluminium, processing:Coating.	<b>Code</b> 84011
360°	37	Cable cover - 2X Material:Rubber, colour:black.	<b>Code</b> 81423
	61 28	Cable cover - 2X Material:Iron, processing:Coating.	<b>Code</b> 81422
	83 119	Cable cover Material:PC, processing:Coating.	<b>Code</b> 81424
	39 18	Closing cap - Electrified black closing plug Material:PC, processing:Coating.	<b>Code</b> 81421
	28 200	Tool	<b>Code</b> 81427



#### Ink system\_L | Lines | Accessories 83990W00

