

Wall Lights | arrayLED 0 W DC - 8 W AC | CRI 80 84186M00





Technical data	
Туре	Surface
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Diffused
Light emission direction	external
Nominal power	0 W DC
Total Power	8 W
Nominal input voltage	220 - 240 V AC
Input voltage range	180 - 264 V AC
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP65
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Radial diffusion
Net weight	0.4 Kg
Electrostatic discharge protection	Yes
Surge protection	1 KV
















Finishing casing	3
Material	Die-cast Aluminium EN AB - 46100
Colour	Dark brown
Processing	Open pore anodizing + Powder Coating

Finishing diffuser	
Material	UV Resistant Polycarbonate
Colour	transparent

Material UV Resista Colour Dark brown	
Colour Dark brown	ant Polycarbonate
	١
Processing Liquid pain	ting