


Shaker



Projectors | 198-264 V
1 arrayLED 23 W DC - 26 W AC | CRI 80
84534M30



Technical data	
Type	Surface
Installation position	Wall lights - Ceiling - Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Medium Flood
Light emission direction	frontal
Nominal power	23 W DC
Total Power	26 W
Source lumens	3424 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	198 - 264 V AC
Frequency	50 - 60 Hz
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP66
IK	IK07
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	Swivelling
total angle (vertical plane)	180 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	2.084 Kg
Electrostatic discharge protection	4 KV
Surge protection	4 KV
Product technological characteristics	Acquastop - TCS

Finishing casing

Material	Die-cast Aluminium EN AB - 46100
Colour	Grey
Processing	Open pore anodizing + Powder Coating

Finishing diffuser

Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening

Finishing bracket

Material	AISI 304 steel
Colour	Grey
Processing	Powder coating

Cables Electrification

Cable connector	No
-----------------	----

Projectors | 198-264 V | 1 arrayLED 23 W DC - 26 W AC | CRI 80 | Base 84534M30

Single emission projectors for outdoor application. The super warm white LED light source with a medium flood light distribution is composed of 1 arrayed LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 3424 lm, with a 148.9 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a grey finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP66; the total weight is of 2.084 kg.

The total absorbed power is 26 W. The power supply cable is included and features a 1 m length.

The device features protection class I and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features

Light Output Ratio (LOR)	72 %
Source lumens	3424 lm
Delivered lumens	2472 lm
Consumption	26 W
Luminaire efficacy	95 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio


L70 B10 C0 252000h (at Tj 65 Ta 25)

UGR

UGR axial	17.9
UGR transversal	17.8
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C0/C180 optics	34°
Light distribution simmetry	Symmetrical




Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.31 0.31	E(0°) 22543 E(C90) 17.2° 9838 E(C0) 17.1° 9847
1.0	0.62 0.62	E(0°) 5636 E(C90) 17.2° 2459 E(C0) 17.1° 2462
1.5	0.93 0.92	E(0°) 2505 E(C90) 17.2° 1093 E(C0) 17.1° 1094
2.0	1.24 1.23	E(0°) 1409 E(C90) 17.2° 615 E(C0) 17.1° 615
2.5	1.55 1.54	E(0°) 902 E(C90) 17.2° 394 E(C0) 17.1° 394
3.0	1.86 1.85	E(0°) 626 E(C90) 17.2° 273 E(C0) 17.1° 274

Distance [m] Cone diameter [m] illuminance [lx]

— C0/C180 (Half-peak divergence: 34.2°)
— C90/C270 (Half-peak divergence: 34.4°)



Shaker | Projectors | Accessories
84534M30



Picket
installation position: land,Cover material: pc

Code
98549