
Baton_P

Pendant Luminaires | arrayLED 0 W DC - 8.2 W AC CRI 90 84575M10





| Technical data | |
|--|---------------------------|
| Туре | Surface |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Light Source | LED |
| Circuit structure | arrayLED |
| Optics | Spot |
| Light emission direction | downward |
| Nominal power | 0 W DC |
| Total Power | 8.2 W |
| Nominal input voltage | 220 - 240 V AC |
| Input voltage range | 100 - 240 V AC |
| CCT / Tone | 2700 K |
| Colour rendering index | 90 Ra |
| C.C. / C.V. | AC |
| Safety class | 2 |
| IP | IP40 |
| IK | IK05 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Driver included | Driver |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 1,8 m |
| Resin potting | No |
| Type of light emission | Single emissior |
| Net weight | 0.9 Kg |
| Electrostatic discharge protection | Yes |
| Surge protection | 0,5 KV |
| Optics technology | Set-back low glare optics |



| Finishing casing | | |
|---------------------|---------------------------------|--|
| Material | Iron - Aluminium 6060 | |
| Colour | White - 5G 9005 Black | |
| Processing | Powder coating - Powder coating | |
| | | |
| Finishing diffuser | | |
| Material | Extra clear glass | |
| Colour | transparent | |
| | | |
| Finishing base | | |
| Material | Iron | |
| Colour | White | |
| Processing | Powder coating | |
| | | |
| Cables Electrificat | tion+suspension | |
| Cable connector | No | |
| Max cable length | 1800 mm | |
| | | |