




Pendant Luminaires | arrayLED 0 W DC - 8.2 W AC
CRI 90
84575M20



Ø 60 |

| Technical data | |
|--|---------------------------|
| Type | Surface |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Light Source | LED |
| Circuit structure | arrayLED |
| Optics | Flood |
| Light emission direction | downward |
| Nominal power | 0 W DC |
| Total Power | 8.2 W |
| Nominal input voltage | 220 - 240 V AC |
| Input voltage range | 100 - 240 V AC |
| CCT / Tone | 2700 K |
| Colour rendering index | 90 Ra |
| C.C. / C.V. | AC |
| Safety class | 2 |
| IP | IP40 |
| IK | IK05 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Driver included | Driver |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 1,8 m |
| Resin potting | No |
| Type of light emission | Single emission |
| Net weight | 0.9 Kg |
| Electrostatic discharge protection | Yes |
| Surge protection | 0,5 KV |
| Optics technology | Set-back low glare optics |

Finishing casing

| | |
|------------|---------------------------------|
| Material | Iron - Aluminium 6060 |
| Colour | White - 5G 9005 Black |
| Processing | Powder coating - Powder coating |

Finishing diffuser

| | |
|----------|-------------------|
| Material | Extra clear glass |
| Colour | transparent |

Finishing base

| | |
|------------|----------------|
| Material | Iron |
| Colour | White |
| Processing | Powder coating |

Cables Electrification+suspension

| | |
|------------------|---------|
| Cable connector | No |
| Max cable length | 1800 mm |