

Pendant Luminaires | arrayLED 0 W DC - 8.2 W AC CRI 90


84578N10





n

7 × × 2 1 × 2 × ×	
Technical data	
Туре	Surface
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Spot
Light emission direction	downward
Nominal power	0 W DC
Total Power	8.2 W
Nominal input voltage	220 - 240 V AC
Input voltage range	100 - 240 V AC
CCT / Tone	4000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP40
IK	IK05
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1,8 m
Resin potting	No
Type of light emission	Single emission
Net weight	1.2 Kg
Electrostatic discharge protection	Yes
Surge protection	0,5 KV
Optics technology	Set-back low glare optics



Finishing casing		
Material	Iron - Aluminium 6060	
Colour	White - 5G 9005 Black	
Processing	Powder coating - Powder coating	
Finishing diffuse	er	
	E (	

Ø 60 | 🔘

rinishing airruser		
Material	Extra clear glass	
Colour	transparent	

Finishing base		
Material	Iron	
Colour	White	
Processing	Powder coating	

Cables Electrification+suspension			
Cable connector	No		
Max cable length	1950 mm		