




Downlights | 3 x powerLED 0 W DC 220 mA | RGB
86613Z60



Technical data











Type	Encasement with flange
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Optics	Wide Flood
Nominal power	0 W DC
Input voltage range	220mA
CCT / Tone	RGB
C.C. / C.V.	CC
Safety class	3
IP	IP44
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	Yes
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.12 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.072 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing

Material	Brass
Colour	nickel
Processing	Brushing



Nitum_R | Downlights | Accessories
86613Z60

 	<p>Outer casing installation position: ceiling; type of installation: masonry L=69mm, H=60mm, D=60mm. Material:ABS Plastic, colour:black.</p>	<p>Code <u>84901</u></p>
	<p>Cable and connector Type of cable power cable; Length 1000 mm; insulation single; section 0.5 mm²; colors: blue - green - red.</p>	<p>Code <u>84866</u></p>
	<p>Cable and connector Type of cable power cable; Length 3000 mm; insulation single; section 0.5 mm²; colors: blue - green - red.</p>	<p>Code <u>84867</u></p>
	<p>Cable and connector Type of cable power cable; Length 1500 mm; insulation single; section 0,35 mm²; colors: blue - green - red.</p>	<p>Code <u>84872</u></p>
	<p>Cable and connector Type of cable power cable; Length 1500 mm; insulation single; section 0,35 mm²; colors: white - black - orange.</p>	<p>Code <u>84873</u></p>
 	<p>Dimmer RF Remote controller</p>	<p>Code <u>C-E700003</u></p>
 	<p>RF remote control</p>	<p>Code <u>C-W600001</u></p>