Periskop45



Projectors | x powerLED 0 W DC 500 mA | CRI 80 90521M30







Technical data	
Туре	Surface
Installation position	Wall lights - Ceiling - Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Flood + Flood + Flood + Flood + Flood
Light emission direction	frontal + frontal + frontal + frontal + frontal
Nominal power	0 W DC
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP .	IP66
ĪK .	IK05
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	Swivelling
total angle (vertical plane)	124 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.2 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	Acquastop - TVS
























Finishing casing		
Material	Die-cast Aluminium EN AB - 46100	
Colour	Grey	
Processing	Open pore anodizing + Powder Coating	

Finishing diffuser	
Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening

Finishing bracket			
Material	Aluminium 5754		
Colour	Anodised Black		
Processing	15 μm Anodizing		

Electronics



99185 On/Off Driver 198~264V AC (1 art.)



C-E200007 On/Off Driver 198~264V AC / 180~275V DC (- art.)

Cables Electrification		
Cable connector	No	

Periskop45



linealight.com

Periskop45 | Projectors | Accessories **90521M30**

		Picket installation position: land,Cover material: aisi 304 steel	Code 98550
	160	Picket - L. 160mm installation position: land,Cover material: aisi 304 steel	Code 98624
	700 F	Picket - L. 700mm installation position: land,Cover material: aisi 304 steel	Code <u>C-F500002</u>
Å	1000 0	Picket - L. 1000mm installation position: land,Cover material: aisi 304 steel	Code <u>C-F500003</u>
		Bag / Fixing kit - Belt for installation on tree	Code 99802