




Wall Lights | 1 x powerLED 0 W DC 630 mA | CRI 80
92312C70



29



| Technical data | |
|--|-------------------|
| Type | Semi-recessed - - |
| Installation position | Wall lights |
| Installation environment | Outdoor |
| Light Source | LED |
| Optics | Wide Flood |
| Light emission direction | downward |
| Nominal power | 0 W DC |
| Input voltage range | 630mA |
| CCT / Tone | 5000 K |
| Colour rendering index | 80 Ra |
| C.C. / C.V. | CC |
| Safety class | 3 |
| IP | IP66 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Driver included | No |
| Dimmable article | DALI - 1-10V |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 1 m |
| Resin potting | Yes |
| Type of light emission | Single emission |
| Net weight | 0.075 Kg |
| Electrostatic discharge protection | No |
| Surge protection | No |

| Finishing casing | |
|------------------|---------|
| Material | Brass |
| Colour | grey |
| Processing | Coating |



Outer casing
installation position: ceiling; type of installation: masonry L=42mm, H=35mm, D=35mm.
Material:ABS Plastic, colour:black.

Code
84336



Outer casing
installation position: wall lights; type of installation: masonry L=49mm, H=60mm, D=60mm.
Material:ABS Plastic, colour:black.

Code
84915