

Uplights | topLED 0 W DC 24 V | CRI 80 95474W00








Technical data		
Туре	Frameless	
Installation position	Wall lights - Floor	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	topLED	
Optics	Diffused	
Nominal power	0 W DC	
Input voltage range	24V	
CCT / Tone	3000 K	
Colour rendering index	80 Ra	
C.C. / C.V.	CV	
Safety class	3	
IP	IP68	
Installation limitations	Not for underwater use	
IK	IK09	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	No	
Dimmable article	DALI - 1-10V	
Directional	No	
Tilting	No	
Walk-over	Yes	
Drive-over	2000 Kg	
Cable included	Yes	
Cable length	1.5 m	
Resin potting	Yes	
Type of light emission	Single emission	
Net weight	0.100 Kg	
Electrostatic discharge protection	No	





Aluminium	
White	
Coating	
	White

Finishing diffuser		
Material	PC	
Colour	transparent	
Processing	Sandblasting	

Surge protection

Orma_FO



Orma_FO | Uplights | Accessories 95474W00





Outer casing

installation position: floor, land; type of installation: masonry L=105mm, H=122mm, D=105mm.

Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.

Finish Code





Outer casing

installation position: floor, land; type of installation: masonry L=43mm, H=80mm, D=43mm. Material:ABS Plastic, colour:black.

Code

98291

98292