Envelope_QW




Wall Lights | topLED 0 W DC | CRI 80 97169N07





Technical data		
Туре	Surface	
Installation position	Wall lights	
Installation environment	Outdoor	
Light Source	LED	
Circuit structure	topLED	
Optics	Asymmetric Wallwasher	
Light emission direction	downward	
Nominal power	0 W DC	
CCT / Tone	4000 K	
Colour rendering index	80 Ra	
C.C. / C.V.	CV	
Safety class	3	
IP	IP66	
IK	IK10	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	No	
Dimmable article	DALI - 1-10V	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	1 m	
Resin potting	Yes	
Type of light emission	Single emission	
Net weight	0.170 Kg	
Electrostatic discharge protection	No	
Surge protection	No	





Finishing casing		
Material	Die-cast Aluminium EN AB - 46100	
Colour	Grey	
Processing	Open pore anodizing + Powder Coating	
Finishing diffuser	•	
Material	Silicone resin	
Colour	transparent	
Cables Electrifica	tion	
Cable connector	No	

Acquastop

Product technological characteristics