




Submerged | x powerLED 0 W DC 500 mA | CRI 80
97317W30



Technical data	
Type	Submerged
Installation position	Wall lights - Ceiling - Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Flood
Light emission direction	upward
Nominal power	0 W DC
Input voltage range	500mA
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP68
Maximum installation depth	20 m
IK	IK10
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	1500 Kg
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.195 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	Acquastop - TVS

Finishing casing	
Material	AISI 316L steel
Colour	steel
Processing	Shot peening

Cables Electrification	
Cable connector	No



Sub_Q | Submerged | Accessories
97317W30



Outer casing - IP68
 installation position: wall lights, floor; type of installation: masonry L=75mm, H=93mm, D=75mm.
 Material:ABS Plastic, colour:black.

Code
98148



Outer casing - Not for underwater use
 installation position: wall lights, floor; type of installation: masonry L=70mm, H=54mm, D=70mm.
 Material:ABS Plastic, colour:black.

Code
98060