


Paseo_X DALI



Lines | 85-277 V

24 x powerLED 17.3 W DC - 19.4 W AC | CRI 80

97612N30



Technical data	
Type	Frameless
Installation position	Wall lights - Ceiling - Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Medium Flood
Light emission direction	upward
Nominal power	17.3 W DC
Total Power	19.4 W
Source lumens	2568 lm
Input voltage range	85 - 277 V AC
Frequency	50 - 60 Hz
CCT / Tone	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP67
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Control unit/Driver
Dimmable article	DALI
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	No
Cable included	Yes
Cable length	0.25 m
Resin potting	No
Type of light emission	Single emission
Net weight	0.89 Kg
Electrostatic discharge protection	4 KV
Surge protection	6 KV
Product technological characteristics	TCS - UV Resistant

Finishing casing	
Material	UV Resistant Polycarbonate
Colour	transparent
Finishing diffuser	
Material	UV Resistant Polycarbonate
Colour	transparent



Lines | 85-277 V | 24 x powerLED 17.3 W DC - 19.4 W AC | CRI 80 | Base 97612N30



Single emission lines for outdoor application. The natural white LED light source with a medium flood light distribution is composed of 24 powered LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 2568 lm, with a 148.4 lm/W nominal luminous efficacy.

The device body is made of uv resistant polycarbonate and features a transparent finish; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP67; the total weight is of 0.89 kg.

The total absorbed power is 17.3 W. The power supply cable is included and features a 0.25 m length.

The device features protection class II and can be wall lights, ceiling or floor-mounted with an outer casing, code 98844(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Energy efficiency class

This product contains 24 light sources of energy efficiency class D.

Illuminotechnical Features

Light Output Ratio (LOR)	81 %
Source lumens	2568 lm
Delivered lumens	2093 lm
Consumption	19.4 W
Luminaire efficacy	107 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25)

UGR

UGR transversal	19.6
UGR axial	16.9
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C0/C180 optics	38°
C90/C270 optics	30°
Light distribution simmetry	Symmetrical 2 assis



	<p>Cable and connector - DMX - Conn. M.5 pin M12 (L 5m) Length 5000 mm; insulation double; cable gland: no; external diameter: 4.5 mm.</p>	<p>Code <u>89189</u></p>
	<p>Cable and connector - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 5m) Length 5000 mm; insulation double; cable gland: no; colors: white - black - blue - brown.</p>	<p>Code <u>89190</u></p>
	<p>Cable and connector - DMX - Conn. M.5 pin M12 + M.3 pin XLR (L 5m) Length 5000 mm; insulation double; cable gland: no.</p>	<p>Code <u>89186</u></p>
	<p>Cable and connector Length 10000 mm; insulation double; cable gland: no.</p>	<p>Code <u>89187</u></p>
	<p>Cable and connector - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 5m) Length 5000 mm; insulation double; cable gland: no.</p>	<p>Code <u>98149</u></p>
	<p>Cable and connector - 24V DC 190-250V AC - Conn M. + F. 4 pin M12 (L 10m) Length 10000 mm; insulation double; cable gland: no.</p>	<p>Code <u>89188</u></p>
	<p>Cable and connector - 24V DC 190-250V AC - Conn. F.4 pin M12 (L 1,5m) Length 1500 mm; insulation double; cable gland: no; colors: white - black - blue - brown.</p>	<p>Code <u>99216</u></p>
	<p>Cable and connector - Extension cable Length 1000 mm; insulation double; cable gland: no.</p>	<p>Code <u>98437</u></p>



	<p>Cable and connector - DMX - Conn. M.5 pin M12 + M.5 pin XLR (L 5m) Length 5000 mm; insulation double; section 0.25 mm²; cable gland: no.</p>	<p>Code 98493</p>
	<p>Cable and connector - DMX - Conn. M.5 pin M12 + F.3 pin XLR (L 5m) Length 5000 mm; insulation double; cable gland: no.</p>	<p>Code 98494</p>
	<p>Outer casing installation position: floor; type of installation: drywall L=1153mm, H=49mm, D=36mm. Material:Aluminium, colour:Anodised Aluminium, processing:Anodisation.</p>	<p>Finish Code 98356</p>
	<p>Outer casing installation position: floor; type of installation: drywall L=1153mm, H=89mm, D=69.5mm. Material:Aluminium, colour:Anodised Aluminium, processing:Anodisation.</p>	<p>Finish Code 98368</p>
	<p>Outer casing - False-ceilings outer-casing installation position: floor; type of installation: drywall L=1155mm, H=55.5mm, D=36mm. Material:Aluminium, colour:Anodised Aluminium, processing:Anodisation.</p>	<p>Finish Code 98375</p>
	<p>Outer casing installation position: floor; type of installation: masonry L=1153mm, H=49mm, D=28mm. Material:Aluminium, colour:Anodised Aluminium, processing:Anodisation.</p>	<p>Finish Code 98469</p>
	<p>Outer casing installation position: floor; type of installation: masonry L=1153mm, H=29.8mm, D=28mm. Material:Aluminium, colour:Anodised Aluminium, processing:Anodisation.</p>	<p>Finish Code 98473</p>
	<p>Outer casing installation position: wall lights; type of installation: masonry L=1153mm, H=66mm, D=32mm. Material:Aluminium, colour:Anodised Aluminium, processing:Anodisation.</p>	<p>Finish Code 98837</p>

Paseo_X DALI




Paseo_X DALI | Lines | Accessories
97612N30

		<p>Outer casing installation position: wall lights; type of installation: masonry L=1157mm, H=91mm, D=64.5mm. Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.</p>	<p>Finish Code <u>98844</u></p>
		<p>Closing cap - two profile end caps</p>	<p>Code <u>98553</u></p>
		<p>Closing cap</p>	<p>Code <u>98554</u></p>
		<p>Closing cap</p>	<p>Code <u>98466</u></p>
		<p>Closing cap</p>	<p>Code <u>98465</u></p>
		<p>Closing cap</p>	<p>Code <u>98464</u></p>
		<p>Closing cap Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.</p>	<p>Code <u>98876</u></p>
		<p>Closing cap Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.</p>	<p>Code <u>98840</u></p>



Paseo_X DALI | Lines | Accessories
97612N30



Closing cap
Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.

Code
98841




Key

Code
98475



Bag / Fixing kit

Code
98771



Bag / Fixing kit

Code
98773