

Beret_X Anti-glaring



Uplights | 1 x powerLED 1 W DC 350 mA | CRI 80
97799M15



Technical data	
Type	Frame
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Spot
Light emission direction	upward
Nominal power	1 W DC
Source lumens	145 lm
Input voltage range	350mA
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP66
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.062 Kg
Electrostatic discharge protection	No
Surge protection	No
Optics technology	Anti - Glare
Product technological characteristics	TVS

Finishing casing

Material	AISI 316L steel
Colour	steel
Processing	Shot peening

Finishing diffuser

Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening

Electronics



89421
On/Off Driver 198-264V AC / 176-275V DC (3 - 6 art.)



89419
On/Off Driver 198-264V AC / 176-275V DC (1 - 2 art.)



C-E200006
On/Off Driver 198-264V AC / 180-275V DC (6 - 12 art.)

Cables Electrification

Cable connector	1
-----------------	---

Beret_X Anti-glaring



Uplights | 1 x powerLED 1 W DC 350 mA | CRI 80 | Base 97799M15

Single emission uplights for outdoor application. The super warm white LED light source with a spot light distribution is composed of 1 powered LED with CCT of 2700 K and a CRI 80; the source luminous flux is 145 lm, with a 145.0 lm/W nominal luminous efficacy.

The device body is made of aisi 316l steel and features a steel finish, processed by means of shot peening; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP66; the total weight is of 0.062 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 1 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted, with a 29 mm diameter hole (in plasterboard) with an outer casing, code 84915(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class D.

Illuminotechnical Features

Light Output Ratio (LOR)	16 %
Source lumens	145 lm
Delivered lumens	24 lm
Consumption	1,0 W
Luminaire efficacy	24 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	1.5 Step
Colour rendering index	80 Ra


Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25)

OPTICAL

C0/C180 optics	22°
Light distribution symmetry	Asymmetrical



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.19	E(0°) 295 E(C0) 142
1.0	0.39	E(0°) 74 E(C0) 35
1.5	0.58	E(0°) 33 E(C0) 16
2.0	0.77	E(0°) 18 E(C0) 9
2.5	0.96	E(0°) 12 E(C0) 6
3.0	1.16	E(0°) 8 E(C0) 4

Distance [m] Cone diameter [m] Illuminance [lx]
— C0/C180 (Half-peak divergence: 21.8°)

Beret_X Anti-glaring



Beret_X Anti-glaring | Uplights | Accessories
97799M15



Outer casing

installation position: wall lights; type of installation: masonry L=49mm, H=60mm, D=60mm.
Material:ABS Plastic, colour:black.

Code

84915



Outer casing

installation position: ceiling; type of installation: masonry L=42mm, H=35mm, D=35mm.
Material:ABS Plastic, colour:black.

Code

84336