





Downlights | 3 x powerLED 12 W DC 350 mA | CRI 90  
**C00151WHNMW**



113 x  
42



## Technical data

Type	Encasement with flange
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	powerLED
Optics	Medium Wide Flood
Light emission direction	downward
Nominal power	12 W DC
Source lumens	1347 lm
Input voltage range	350mA
CCT / Tone	4000 K
Colour rendering index	90 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.170 m
Resin potting	No
Type of light emission	Single emission
Net weight	0.36 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	TVS

## Finishing casing

Material	Iron
Colour	White + Black
Processing	Powder coating

## Finishing diffuser

Material	Pet
Colour	White

## Finishing radiator

Material	Die-cast Aluminium EN AB - 46100
Processing	Tumbling

## Electronics



99115  
1-10V - N/O button Multi Power 198~264V AC / 180~275V DC (1 art.)



99375  
On/Off Driver 198~264V AC (1 art.)



83322  
Push and Simply Dim - DALI-2 Controller (1 art.)

## Downlights | 3 x powerLED 12 W DC 350 mA | CRI 90 | Base C00151WHNMW


Single emission recessed downlights for indoor application. The natural white LED light source with a medium wide flood light distribution is composed of 3 powerLED LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 1347 lm, with a 112.3 lm/W nominal luminous efficacy.

The device body is made of iron and features a white + black finish, processed by means of powder coating; the diffuser is made of pet. The ingress protection degree is IP20; the total weight is of 0.36 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 12 W. The power supply cable is included and features a 0.170 m length.

The device features protection class III and can be ceiling-mounted, with a 113 x 42 mm hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.43 0.44	E(0°) 5432 E(C90) 2112 E(C0) 2087
1.0	0.87 0.88	E(0°) 1358 E(C90) 528 E(C0) 522
1.5	1.30 1.32	E(0°) 604 E(C90) 235 E(C0) 232
2.0	1.74 1.76	E(0°) 339 E(C90) 132 E(C0) 130
2.5	2.17 2.21	E(0°) 217 E(C90) 84 E(C0) 83
3.0	2.61 2.65	E(0°) 151 E(C90) 59 E(C0) 58

— C0/C180 (Half-peak divergence: 47.6°)  
— C90/C270 (Half-peak divergence: 47.0°)

### Energy efficiency class

This product contains 3 light sources of energy efficiency class F.

### Illuminotechnical Features

Light Output Ratio (LOR)	56 %
Source lumens	1347 lm
Delivered lumens	762 lm
Consumption	12 W
Luminaire efficacy	63 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Black Body Locus	On
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

### LED Life / Failure Ratio

L70 B10 C0 247450h (at Tj 60 Ta 25 )

### UGR

UGR axial	11.4
UGR transversal	12.1
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C0/C180 optics	47°
Light distribution simmetry	Symmetrical

