


LED Strip | 600 topLED 96 W DC 24 V | 19.2 W/m 0 Lm/m | CRI >90 | RGBW - 3000 **C00417WHVDI**









Technical data	
Length	5000 mm
Minimum cut	100 mm
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward
Nominal power	96 W DC
Input voltage range	24V
CCT / Tone	RGBW - 3000 K
Colour rendering index	>90 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	Yes
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.3 m
Resin potting	No
Type of light emission	Single emission
Length	5000 mm
Net weight	0.09 Kg
Electrostatic discharge protection	No
Surge protection	No

100	X

₩ [**||** (€ 🕱 💍 🔁 🖟 C.V. 🛱 ||P20 | **™** 🔝

Finishing cas	sing	
Colour	white	

Electronics



99331 On/Off Driver 198~264V AC / 176~275V DC 150 W (1 art.)



99332 1-10V Controller (1 art.)



C-E700005 DMX-RDM Multi Channel 10.8~26.4V DC W (1 art.)

Cables Electrification				
Cable connector	No			
Luman BCBW				

Lumen RGBV	V			
N. Led	Red	Green	Blue	white
600	729 lm	1449 lm	373 lm	3469 lm



LED Strip | 600 topLED 96 W DC 24 V | 19.2 W/m | 0 Lm/m | CRI >90 | RGBW - 3000 C00417WHVDI

Single emission led strip for indoor application. The RGBW - 3000 K LED light source with a diffused light distribution is composed of 600 topled LEDs with CCT of RGB-W 3000 K and a CRI >90.

The device body and features a white finish. The ingress protection degree is IP20; the total weight is of 0.09 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 96 W. The power supply cable is included and features a 0.3 m length.

The device features protection class III and can be wall lights or ceilingmounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class F.

Illuminotechnical Features

Standard Deviation of Colour Matching

3 Step MacAdam



LED Strip | 600 topLED 96 W DC 24 V | 19.2 W/m | 0 Lm/m | CRI >90 | RGBW - 3000 C00417WHVDI

Components





LUNO_20/27 - Profili | Modular

Code

C-K100017






LUNO_20/27

Code

C-K100018






Rive_17/16 - Profili | Modular

Code

C-K100015






Rive_17/16 - Profili | Modular

Code

C-K100016





Cela_18/18 - Profili | Modular

Code

C-K100019





Cela_18/18 - Profili | Modular

Code

C-K100020





Tabulo_35/14 - Profili | Modular

Code

C-K100025





Fylo+ Recessed_5

Code

65012 - 65013



65015 - 65016

LED Strip | 600 topLED 96 W DC 24 V | 19.2 W/m | 0 Lm/m | CRI >90 | RGBW - 3000 C00417WHVDI

Components



Fylo+ Surface_1



LED Strip | 600 topLED 96 W DC 24 V | 19.2 W/m | 0 Lm/m | CRI >90 | RGBW - 3000 C00417WHVDI

Components





Fylo+ Surface_4

Code

65024 - 65025



5x	30 0	Springs for recessing - 5 pieces	Code 98420
	2,5 T8	Diffuser Diffuser Type: opaline diffuser. Material:PC, colour:opaline.	Finish Code Opaline 98395
	19 7869	Diffuser	Code 98941
	** 15 2000	Diffuser	Code 98942
	** 15	Diffuser - Opaline Diffuser	Code 98943
	a)	Diffuser	Code 98898
	a)	Diffuser	Code 98899
	M 2000	Diffuser	Code 98900



	n 11 2005	Diffuser	Code 98917
	11.3 25000	Diffuser	Code 98925
	o)	Diffuser Material:PC, colour:black.	Finish Code Black 83132
	21 2000	Diffuser Material:PC, colour:opaline.	Finish Code Opaline C-K200001
	9 2000	Diffuser Material:PC, colour:black.	Finish Code Black C-K200002
	77 2000	Diffuser Material:PC, colour:opaline.	Finish Code Opaline C-K200003
	77 2000	Diffuser Material:PC, colour:black.	Finish Code Black C-K200004
17		Diffuser Material:PC, colour:opaline.	Finish Code Opaline C-K200005



± 17		Diffuser Material:PC, colour:opaline.	Finish Code Opaline C-K200007
27 2000		Diffuser Material:PC, colour:black.	Finish Code Black C-K200009
	14 24.5 10.2 6 a	Closing cap	Code 98418
	2	Closing cap - Closing cap Material:PC, colour:white.	Code 98892
	2 0 17	Closing cap	Code 98928
	26	Closing cap	Code 98896
	p 0 0 0	Closing cap	Code 98902
	2	Closing cap Material:Aluminium, colour:translucent.	Code 98907



	2	Closing cap Material:PC, colour:white.	Code 98922
	9 0 1	Closing cap Material:PC, colour:white.	Code 98918
44	2 72	Closing cap Material:PC, colour:black.	Code 83133
		Closing cap Material:plastic, colour:grey.	Code C-V400023
	20.5	Closing cap Material:plastic, colour:grey.	Code C-V400019
	b2	Closing cap Material:ABS Plastic, colour:black.	Code C-V400020
	E	Closing cap Material:plastic, colour:grey.	Code C-V400021
		Closing cap Material:ABS Plastic, colour:black.	Code C-V400022



10 10 10 10 10 10 10 10 10 10 10 10 10 1	Closing cap Material:plastic, colour:grey.	Code C-V400025
	Closing cap Material:plastic, colour:grey.	Code <u>C-V400027</u>
	Closing cap Material:plastic, colour:grey.	Code C-V400029
	Closing cap Material:plastic, colour:grey.	Code C-V400031
5	Closing cap Material:plastic, colour:grey.	Code C-V400033
	Closing cap Material:plastic, colour:grey.	Code C-V400035
	Closing cap Material:ABS Plastic, colour:black.	Code <u>C-V400036</u>
	Closing cap Material:ABS Plastic, colour:black.	Code <u>C-V400038</u>



Ribbon Plus RGBW | LED Strip | Accessories C00417WHVDI





Closing cap
Material:plastic, colour:grey.

Code

C-V400037





Closing cap

Material:plastic, colour:grey.

Code

C-V400041





Bracket - Mounting bracket
L=19mm, H=8mm, D=9mm.
Material:Iron, colour:zinc, processing:Washing.

Code

98944





Bracket
L=9mm, H=8.8mm, D=21.8mm.
Material:Iron, colour:translucent, processing:Washing.

Code

98931





Bracket
L=22mm, H=21.5mm, D=16.4mm.
Material:PC, colour:transparent.

Finish

Code

Transp. 98904





Bracket
L=12mm, H=15mm, D=30mm.
Material:PC, colour:white.

Finish White Code

98901





Profile - Wall integrated side profile

Material:Aluminium 6060, colour:Anodised Aluminum, processing:20 µm anodizing.

Code 98921





Connector - Fast connector 5 poles for Ribbon Plus RGBW Length 22 mm.

Code

83403



THE REAL PROPERTY.	00 E 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	Connector - Fast connector 5 poles for Ribbon Plus RGBW Length 18,2 mm.	Code 83402
		Optics Light distribution: medium flood,Cover material: pc	Code C-U100001
5	17 2 5000 17 2 5000	Bag / Fixing kit	Code C-K100027
	18,1 2000	Bag / Fixing kit	Code C-K100028
	18,1 2000	Bag / Fixing kit	Code C-K100029