


LED Strip | 1 topLED 72 W DC 24 V | 14.4 W/m 1730 Lm/m | CRI 90  $\,$ 

#### C0041NDI05000









| Technical data                                 |                          |
|--|--------------------------|
| Length   | 5000 mm                  |
| Minimum cut                                    | 42 mm                    |
| Type   | LED Strip                |
| Installation position                          | Wall lights -<br>Ceiling |
| Installation environment                       | Indoor                   |
| Light Source                                   | LED                      |
| Circuit structure                              | topLED                   |
| Optics   | Diffused                 |
| Light emission direction                       | external                 |
| Nominal power                                  | 72 W DC                  |
| Power / m                                      | 14.4 W / m               |
| Source lumens                                  | 8650 lm                  |
| Source lumens / m                              | 1730 lm / m              |
| Input voltage range                            | 24V                      |
| CCT / Tone                                     | 4000 K                   |
| Colour rendering index                         | 90 Ra                    |
| C.C. / C.V.                                    | CV                       |
| Safety class                                   | 3                        |
| IP   | IP20                     |
| Glow wire test                                 | No                       |
| Direct mounting on normally flammable surfaces | Yes                      |
| CE   | Yes                      |
| Driver included                                | No                       |
| Dimmable article                               | DALI - 1-10V             |
| Directional                                    | No                       |
| Tilting  | No                       |
| Walk-over                                      | No                       |
| Drive-over                                     | No                       |
| Cable included                                 | Yes                      |
| Cable length                                   | 0.2 m                    |
| Resin potting                                  | No                       |
| Type of light emission                         | Single emission          |
| Length   | 5000 mm                  |
| Net weight                                     | 0.36 Kg                  |
| Electrostatic discharge protection             | No                       |
| Surge protection                               | No                       |

| Technopolymer |
|---------------|
| white         |
|               |

#### Electronics



99331 On/Off Driver 198~264V AC / 176~275V DC 150 W (1 - 2 art.)



1-10V Controller (1 - 2 art.)



99374 On/Off Driver 198~264V AC / 176~275V DC 75 W (1



83333 Push and Simply Dim - DALI-2 Controller (1 - 2 art.)



C-E400002 Push and Simply Dim - DALI-2 Controller (1 - 3 art.)



#### LED Strip | 1 topLED 72 W DC 24 V | 14.4 W/m | 1730 Lm/m | CRI 90 **C0041NDI05000**

Single emission led strip for indoor application. The natural white LED light source with a diffused light distribution is composed of 840 stripled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 8650 lm, with a 120.1 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish. The ingress protection degree is IP20; the total weight is of 0.36 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 72 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

#### Energy efficiency class

This product contains a light source of energy efficiency class E.

| Illuminotechnical Features             |                |
|--|----------------|
| Source lumens                          | 8650 lm        |
| Colour temperature                     | 4000 K         |
| Standard Deviation of Colour Matching  | 3 Step MacAdam |
| Colour rendering index                 | 90 Ra          |
|  |                |
| Standard Operating Ambient Temperature | -20 / +45°C    |

#### LED Life / Failure Ratio

L70 B50 C0 50000h





LED Strip | 1 topLED 72 W DC 24 V | 14.4 W/m | 1730 Lm/m | CRI 90  ${\bf C0041NDI05000}$ 

#### Components





LUNO\_20/27 - Profili | Modular

Code

C-K100017






LUNO\_20/27 - Profili | Modular

Code

C-K100018






Rive\_17/16 - Profili | Modular

Code

C-K100015





Rive\_17/16 - Profili | Modular

Code

C-K100016





Cela\_18/18 - Profili | Modular

Code

C-K100019





Cela\_18/18 - Profili | Modular

Code

C-K100020






Tabulo\_35/14 - Profili | Modular

Code

C-K100025





Rive\_17/16


**Code** C-K100026 - C-K100027



LED Strip | 1 topLED 72 W DC 24 V | 14.4 W/m | 1730 Lm/m | CRI 90 **C0041NDI05000** 

#### Components





Cela\_18/18

Code

C-K100028 - C-K100029



| The same of the sa | 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 | Connector<br>Length 15,4 mm.                               |                 | <b>Code</b><br>83399   |
|--|---|--|-----------------|------------------------|
|  | o) 15 2000                              | Diffuser   |                 | <b>Code</b><br>98941   |
|  | ol 19 2000                              | Diffuser   |                 | <b>Code</b> 98942      |
|  | ol 15 2000                              | Diffuser - Opaline Diffuser                                |                 | <b>Code</b> 98943      |
|  | o) 15 2000                              | Diffuser<br>Material:PC, colour:black.                     | Finish<br>Black | <b>Code</b><br>83132   |
|  | 16                                      | Optics Light distribution: medium flood,Cover material: pc |                 | <b>ode</b><br>-U100001 |
| 0 0  |   | Diffuser<br>Material:PC, colour:opaline.                   |                 | <b>ode</b><br>-K200005 |
| ±  |   | Diffuser<br>Material:PC, colour:opaline.                   |                 | <b>ode</b><br>-K200007 |



|    | 2      | Closing cap - Closing cap<br>Material:PC, colour:white.  | <b>Code</b><br>98892            |
|----|--------|--|---------------------------------|
| ** |        | Closing cap Material:PC, colour:black.   | <b>Code</b><br>83133            |
|    |        | Closing cap Material:plastic, colour:grey.   | <b>Code</b><br><u>C-V400023</u> |
|    |        | Closing cap Material:plastic, colour:grey.   | <b>Code</b><br><u>C-V400027</u> |
|    |        | Closing cap Material:plastic, colour:grey.   | <b>Code</b><br>C-V400029        |
|    | - 10   | Bracket - Mounting bracket L=19mm, H=8mm, D=9mm. Material:Iron, colour:zinc, processing:Washing. | <b>Code</b><br>98944            |
|    | 9 7000 | Diffuser   | <b>Code</b><br>98925            |
|    |        | Closing cap  | <b>Code</b><br>98928            |



|   | 10 21 2000      | Diffuser<br>Material:PC, colour:opaline.   | Finish Opaline         | <b>Code</b><br>C-K200001 |
|---|-----------------|--|------------------------|--------------------------|
|   | 18 2000         | Diffuser<br>Material:PC, colour:black.   | <b>Finish</b><br>Black | <b>Code</b><br>C-K200002 |
|   | 2 214           | Bracket L=9mm, H=8.8mm, D=21.8mm. Material:Iron, colour:translucent, processing:Washing. |                        | <b>Code</b><br>98931     |
|   | 21 2000         | Diffuser<br>Material:PC, colour:opaline.   | Finish Opaline         | <b>Code</b><br>C-K200003 |
|   | 77              | Diffuser<br>Material:PC, colour:black.   | <b>Finish</b><br>Black | <b>Code</b><br>C-K200004 |
|   |                 | Closing cap Material:plastic, colour:grey.   |                        | <b>Code</b><br>C-V400035 |
|   |                 | Closing cap<br>Material:ABS Plastic, colour:black.                                       |                        | <b>Code</b><br>C-V400036 |
| 4 | 10 TO 10 TO 104 | Closing cap Material:plastic, colour:grey.   |                        | <b>Code</b><br>C-V400025 |



|   |  | Closing cap<br>Material:plastic, colour:grey. | <b>Code</b><br>C-V400031 |
|---|--|---|--------------------------|
|   | 2) 29 10 10 10 10 10 10 10 10 10 10 10 10 10 | Closing cap<br>Material:plastic, colour:grey. | <b>Code</b><br>C-V400033 |
| 5 | 90 17.2 2000                                 | Bag / Fixing kit                              | <b>Code</b><br>C-K100027 |
|   |  | Closing cap                                   | <b>Code</b><br>98896     |
|   | e 24 2000                                    | Diffuser                                      | <b>Code</b><br>98898     |
|   | 24 2509                                      | Diffuser                                      | Code<br>98899            |
|   | 24 200                                       | Diffuser                                      | Code<br>98900            |
|   |  | Closing cap                                   | <b>Code</b><br>98902     |



# Ribbon HF\_V2 168 LEDs/m | LED Strip | Accessories **C0041NDI05000**

|         | 20 Co                                   | Proglet  | nish Code<br>nite 98901  |
|---------|---|--|--------------------------|
|         |   | Closing cap Material:Aluminium, colour:translucent.  | <b>Code</b><br>98907     |
|         | 11 2005                                 | Diffuser   | <b>Code</b><br>98917     |
|         | y                                       | Closing cap<br>Material:PC, colour:white.  | <b>Code</b><br>98918     |
|         | 35,2 2000                               | Profile - Wall integrated side profile<br>Material:Aluminium 6060, colour:Anodised Aluminum, processing:20 µm anodizing. | <b>Code</b><br>98921     |
|         |   | Closing cap<br>Material:PC, colour:white.  | <b>Code</b><br>98922     |
| 27 2900 |   | Diffuser Material:PC, colour:black.  | <b>Code</b><br>C-K200009 |
|         | R 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | Closing cap Material:plastic, colour:grey.   | <b>Code</b><br>C-V400041 |



|    | 2,5 = 18   | Diffuser Diffuser Type: opaline diffuser. Material:PC, colour:opaline. | Finish Code Opaline 98395       |
|----|--|--|---------------------------------|
|    | 24.5<br>10.2 6 0   | Closing cap  | <b>Code</b> 98418               |
| 5x | 25<br>30 0<br>6.8 \  | Springs for recessing - 5 pieces                                       | <b>Code</b> 98420               |
|    | 18 15 15 10 4 5 TO THE STATE OF | Closing cap Material:plastic, colour:grey.                             | <b>Code</b><br>C-V400037        |
| 60 |  | Closing cap  Material:ABS Plastic, colour:black.                       | <b>Code</b><br>C-V400038        |
|    | 22 16.4  | Bracket L=22mm, H=21.5mm, D=16.4mm. Material:PC, colour:transparent.   | Finish Code Transp. 98904       |
|    | 18,1 2000  | Bag / Fixing kit   | <b>Code</b><br><u>C-K100028</u> |
|    | 18,1 2000  | Bag / Fixing kit   | <b>Code</b><br>C-K100029        |



| Carlotte Marie Carlotte Carlot | 8CH80-2  82  81  1   1   1   2   2   2   2   2   2   2   | Connector - Fast connector for Ribbon Basic V2 8mm, Ribbon HD 8mm (not Ribbon COB) Length 21,6 mm. | <b>Code</b><br>83396     |
|--|--|--|--------------------------|
| To the state of th | 3.60<br>- 3.60<br>- 5.30<br>- 5. | Connector - Fast connector for Ribbon Basic V2 8mm, Ribbon HD 8mm (not Ribbon COB) Length 15,4 mm. | <b>Code</b><br>83397     |
|  |  | Connector - Quick strip-strip connector for Ribbon HF V2<br>Length 15 mm.                          | <b>Code</b><br>C-W400001 |
|  |  | Connector - Quick cable-strip connector for Ribbon HF V2 Length 15 mm.                             | <b>Code</b><br>C-W400002 |
|  | 20.5   | Closing cap  Material:plastic, colour:grey.  | <b>Code</b><br>C-V400019 |
|  |  | Closing cap Material:ABS Plastic, colour:black.  | <b>Code</b><br>C-V400020 |
|  | F2   | Closing cap Material:plastic, colour:grey.   | <b>Code</b><br>C-V400021 |
| <b>6</b>   |  | Closing cap  Material:ABS Plastic, colour:black.   | <b>Code</b><br>C-V400022 |

