

LED Strip | 1 topLED 108 W DC 24 V | 21.6 W/m 3037.4 Lm/m | CRI 83+

C0044NDI05000








Technical data	
Length	5000 mm
Minimum cut	50 mm
Туре	LED Strip
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	external
Nominal power	108 W DC
Power / m	21.6 W / m
Source lumens	15187 lm
Source lumens / m	3037.4 lm / m
Input voltage range	24V
CCT / Tone	4000 K
Colour rendering index	83+ Ra
C.C. / C.V.	CV
Safety class	3
IP	IP20
Glow wire test	No
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.2 m
Resin potting	No
Type of light emission	Single emission
Length	5000 mm
Net weight	0.17 Kg
Electrostatic discharge protection	No
Surge protection	No





Finishing casing		
Material	Technopolymer	
Colour	white	

Electronics



99331 On/Off Driver 198~264V AC / 176~275V DC 150 W (1 art.)



1-10V Controller (1 art.)



99374 On/Off Driver 198~264V AC / 176~275V DC 75 W (1



83333

Push and Simply Dim - DALI-2 Controller (1 art.)



C-E400002

Push and Simply Dim - DALI-2 Controller (1 - 2 art.)



LED Strip | 1 topLED 108 W DC 24 V | 21.6 W/m | 3037.4 Lm/m | CRI 83+ ${\bf C0044NDI05000}$

Single emission led strip for indoor application. The natural white LED light source with a diffused light distribution is composed of 800 stripled LEDs with CCT of 4000 K and a CRI 83+; the source luminous flux is 15187 lm, with a 140.6 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish. The ingress protection degree is IP20; the total weight is of 0.17 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 108 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be wall lights or ceilingmounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features	
Source lumens	15187 lm
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Standard Operating Ambient Temperature	-20 / +45°C

LED Life / Failure Ratio

L70 B50 C0 54000h





LED Strip | 1 topLED 108 W DC 24 V | 21.6 W/m | 3037.4 Lm/m | CRI 83+ ${\bf C0044NDI05000}$

Components





LUNO_20/27 - Profili | Modular

Code

C-K100017






LUNO_20/27 - Profili | Modular

Code

C-K100018






Rive_17/16 - Profili | Modular

Code

C-K100015





Rive_17/16 - Profili | Modular

Code

C-K100016





Cela_18/18 - Profili | Modular

Code

C-K100019





Cela_18/18 - Profili | Modular

Code

C-K100020





Tabulo_35/14 - Profili | Modular

Code

C-K100025



Egina V	5 00 00 00 00 00 00 00 00 00 00 00 00 00	Connector Length 15,4 mm.	Code 83399
	15 2000	Diffuser	Code 98941
	6 2000	Diffuser	Code 98942
	9 2000	Diffuser - Opaline Diffuser	Code 98943
	9 2000	Diffuser Material:PC, colour:black.	Finish Code Black 83132
		Optics Light distribution: medium flood,Cover material: pc	Code <u>C-U100001</u>
17		Diffuser Material:PC, colour:opaline.	Finish Code Opaline C-K200005
± 17 2000 ±		Diffuser Material:PC, colour:opaline.	Finish Code Opaline C-K200007



Ribbon HE 160 LEDs/m | LED Strip | Accessories **C0044NDI05000**

5/10 23.12.2024

	2	Closing cap - Closing cap Material:PC, colour:white.	Code 98892
49		Closing cap Material:PC, colour:black.	Code 83133
		Closing cap Material:plastic, colour:grey.	Code <u>C-V400023</u>
		Closing cap Material:plastic, colour:grey.	Code <u>C-V400027</u>
		Closing cap Material:plastic, colour:grey.	Code C-V400029
	-	Bracket - Mounting bracket L=19mm, H=8mm, D=9mm. Material:Iron, colour:zinc, processing:Washing.	Code 98944
	9 200	Diffuser	Code 98925
		Closing cap	Code 98928



	10 21 2000 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Diffuser Material:PC, colour:opaline.	Finish Opaline	Code C-K200001
	21 2000	Diffuser Material:PC, colour:black.	Finish Black	Code C-K200002
	2	Bracket L=9mm, H=8.8mm, D=21.8mm. Material:Iron, colour:translucent, processing:Washing.		Code 98931
	77 21 2000	Diffuser Material:PC, colour:opaline.	Finish Opaline	Code C-K200003
	77 2000	Diffuser Material:PC, colour:black.	Finish Black	Code C-K200004
		Closing cap Material:plastic, colour:grey.		Code C-V400035
		Closing cap Material:ABS Plastic, colour:black.		Code C-V400036
4	16 1 10 10 10 10 10 10 10 10 10 10 10 10 1	Closing cap Material:plastic, colour:grey.		Code C-V400025



		Closing cap Material:plastic, colour:grey.	Code C-V400031
	20 20 20 10 to 10	Closing cap Material:plastic, colour:grey.	Code C-V400033
-	# 17.2 5000	Bag / Fixing kit	Code C-K100027
		Closing cap	Code 98896
	e	Diffuser	Code 98898
	24 3000	Diffuser	Code 98899
	24 2000	Diffuser	Code 98900
		Closing cap	Code 98902



	5 0	Procket	18 10	Code 98901
		Closing cap Material:Aluminium, colour:translucent.		Code 98907
	n	Diffuser		Code 98917
	# O O O	Closing cap Material:PC, colour:white.		Code 98918
	35,2 2000	Profile - Wall integrated side profile Material:Aluminium 6060, colour:Anodised Aluminum, processing:20 µm anodizing.		Code 98921
	2	Closing cap Material:PC, colour:white.		Code 98922
27 2000		Diffuser Material:PC, colour:black.	Code C-K2	e 200009
		Closing cap Material:plastic, colour:grey.	Code C-V4	e 400041



	2.5 1 8	Diffuser Diffuser Type: opaline diffuser. Material:PC, colour:opaline.	Finish Code Opaline 98395
	14 24.5 10.2 6 a e	Closing cap	Code 98418
5x	30 0	Springs for recessing - 5 pieces	Code 98420
	10 25 25 10 4 5 1 5 1 5 1 5 1 5 1 5 1 5 1 5 1 5 1 5	Closing cap Material:plastic, colour:grey.	Code C-V400037
		Closing cap Material:ABS Plastic, colour:black.	Code C-V400038
	22 1944	Bracket L=22mm, H=21.5mm, D=16.4mm. Material:PC, colour:transparent.	Finish Code Transp. 98904
	18,1 2000	Bag / Fixing kit	Code <u>C-K100028</u>
	18,1 2000	Bag / Fixing kit	Code <u>C-K100029</u>



SA WILLIAM WAR AND THE SAN AND	8CH886-3 \$1 \$2 \$1 \$2 \$3.50 \$5.5	Connector - Fast connector for Ribbon Basic V2 8mm, Ribbon HD 8mm (not Ribbon COB) Length 21,6 mm.	Code 83396
Hi de la	1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00	Connector - Fast connector for Ribbon Basic V2 8mm, Ribbon HD 8mm (not Ribbon COB) Length 15,4 mm.	Code 83397
The state of the state of	1.00 - 1.00 10.30 10.30 - 10.30 - 10.3	Connector - Fast connector for Ribbon Plus 10mm - Ribbon PRO - Ribbon PRO 48V Length 21,6 mm.	Code 83398
	72	Closing cap Material:plastic, colour:grey.	Code C-V400019
	783	Closing cap Material:ABS Plastic, colour:black.	Code C-V400020
	72	Closing cap Material:plastic, colour:grey.	Code C-V400021
9	70.5	Closing cap Material:ABS Plastic, colour:black.	Code C-V400022