




Downlights | 1 arrayLED 9 W DC 700 mA | CRI 90
C00613CUWMW



64



Max inclination:
 +20° with double panel
 +30° with single panel

Technical data

Type	Encasement with flange
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Medium Wide Flood
Light emission direction	downward
Nominal power	9 W DC
Source lumens	1119 lm
Input voltage range	700mA
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP40
Optical compartment IP	IP65
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	Yes
total angle (horizontal plane)	360 °
total angle (vertical plane)	30 °
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.2 m
Resin potting	No
Type of light emission	Single emission
Net weight	0.3 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing

Material	Technopolymer
Colour	copper
Processing	Coating

Finishing diffuser

Material	UV Resistant Polycarbonate
Colour	transparent

Finishing radiator

Material	Die-cast Aluminium EN AB - 46100
Colour	Aluminium
Processing	Polishing

Electronics

- 
99147
On/Off Driver 198-264V AC (1 - 2 art.)

- 
99735
Multi Power 198-264V AC / 180-275V DC (1 art.)

- 
99733
1-10V Multi Power 198-264V AC / 180-275V DC (1 art.)

- 
C-E100012
Push and Simply Dim - DALI-2 Controller (1 art.)

- 
C-E100016
Push and Simply Dim - DALI-2 Controller (1 - 2 art.)



Downlights | 1 arrayLED 9 W DC 700 mA | CRI 90 | Base C00613CUWMW

Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features

Light Output Ratio (LOR)	49 %
Source lumens	1119 lm
Delivered lumens	555 lm
Consumption	9 W
Luminaire efficacy	61 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	90 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio

L70 B10 C0 112960h (at Tj 65 Ta 25)

UGR

UGR axial	6.5
UGR transversal	6.5
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C0/C180 optics	40°
Light distribution simmetry	Symmetrical



Single emission recessed downlights for indoor application. The warm white LED light source with a medium wide flood light distribution is composed of 1 arrayed LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1119 lm, with a 124.3 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a copper finish, processed by means of coating; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP40; the total weight is of 0.3 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 9 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be ceiling-mounted, with a 64 mm diameter hole (in plasterboard) with an outer casing, code 99849(for concrete or masonry).









Compliant with the EN 60598-1 standard and its specific provisions.





		<p>Outer casing installation position: ceiling; type of installation: masonry L=200mm, H=113mm, D=137mm. Material:polypropylene, colour:white.</p>	<p>Code <u>89373</u></p>
		<p>Outer casing installation position: ceiling; type of installation: masonry L=370mm, H=120mm, D=200mm. Material:polypropylene, colour:white.</p>	<p>Code <u>89374</u></p>
		<p>Outer casing installation position: ceiling; type of installation: drywall L=77.5mm, H=28mm, D=77.5mm. Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.</p>	<p>Finish Code <u>99849</u></p>
		<p>Optics Light distribution: medium wide flood,Cover material: uv resistant polycarbonate</p>	<p>Code <u>83372</u></p>
		<p>Optics Light distribution: medium flood,Cover material: uv resistant polycarbonate</p>	<p>Code <u>83371</u></p>
		<p>Optics Light distribution: spot,Cover material: uv resistant polycarbonate</p>	<p>Code <u>83370</u></p>
		<p>Anti-glare Anti-glare Type: honeycomb louvre. Material:Pom-C, colour:Black.</p>	<p>Code <u>83367</u></p>
		<p>Diffuser Diffuser Type: elliptical filter</p>	<p>Code <u>83368</u></p>



	Diffuser Diffuser Type: aesthetic filter	Code <u>83369</u>
	Warp_QJ EVO black front kit	Code <u>C-K400094</u>
	Quantum_RJ EVO gold front kit	Code <u>C-K400110</u>
	Quantum_RJ EVO copper front kit	Code <u>C-K400111</u>
	Vos_RJ EVO copper front kit	Code <u>C-K400109</u>
	Vos_RJ EVO gold front kit	Code <u>C-K400108</u>
	Warp_RJ EVO gold front kit	Code <u>C-K400028</u>
	Warp_RJ EVO copper front kit	Code <u>C-K400029</u>



Warp_QJ EVO black front kit

Code
C-K400082



Warp_QJ EVO white front kit

Code
C-K400081



Quantum_RJ EVO black front kit

Code
C-K400088



Quantum_RJ EVO white front kit

Code
C-K400087



Vos_RJ EVO black front kit

Code
C-K400084



Vos_RJ EVO white front kit

Code
C-K400083