




Downlights | 1 arrayLED 14 W DC 400 mA | CRI 80
C00641BBAFL



92



Max inclination:
 +20° with double panel
 +30° with single panel

Technical data

Type	Encasement with flange
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Flood
Light emission direction	downward
Nominal power	14 W DC
Source lumens	2007 lm
Input voltage range	400mA
CCT / Tone	2200 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP40
Optical compartment IP	IP65
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	Yes
total angle (horizontal plane)	360 °
total angle (vertical plane)	30 °
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.2 m
Resin potting	No
Type of light emission	Single emission
Net weight	0.35 Kg
Electrostatic discharge protection	No
Surge protection	No
Optics technology	Honey comb

Finishing casing

Material	Technopolymer
Colour	Black
Processing	Coating


Finishing diffuser


Material	UV Resistant Polycarbonate
Colour	transparent

Finishing radiator

Material	Die-cast Aluminium EN AB - 46100
Colour	Aluminium
Processing	Polishing

Electronics

 99734
 Multi Power 198~264V AC / 180~275V DC (1 art.)

 99732
 1-10V Multi Power 198~264V AC / 180~275V DC (1 art.)

 83322
 Push and Simply Dim - DALI-2 Controller (1 art.)



Downlights | 1 arrayLED 14 W DC 400 mA | CRI 80 | Base
C00641BBAFL

Single emission recessed downlights for indoor application. The ancient white LED light source with a flood light distribution is composed of 1 arrayed LEDs with CCT of 2200 K and a CRI 80; the source luminous flux is 2007 lm, with a 143.4 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a black finish, processed by means of coating; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP40; the total weight is of 0.35 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 14 W. The power supply cable is included and features a 0.2 m length.

The device features protection class III and can be ceiling-mounted, with a 92 mm diameter hole (in plasterboard) with an outer casing, code 83065(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features

Light Output Ratio (LOR)	42 %
Source lumens	2007 lm
Delivered lumens	857 lm
Consumption	14 W
Luminaire efficacy	61 lm/W
Colour temperature	2200 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio



L70 B10 C0 252000h (at Tj 65 Ta 25)

UGR

UGR axial	0.7
UGR transversal	0.7
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C0/C180 optics	20°
Light distribution simmetry	Symmetrical





Quantum_RJ EVO copper front kit

Code
C-K400105



Quantum_RJ EVO gold front kit

Code
C-K400104



Quantum_RJ EVO black front kit

Code
C-K400090



Quantum_RJ EVO white front kit

Code
C-K400089



Vos_RJ EVO copper front kit

Code
C-K400103



Vos_RJ EVO gold front kit

Code
C-K400102



Vos_RJ EVO black front kit









Code
C-K400086



Vos_RJ EVO white front kit


Code
C-K400085



	Warp_RJ EVO copper front kit	Code <u>C-K400115</u>
	Warp_RJ EVO gold front kit	Code <u>C-K400114</u>
	Warp_RJ EVO black front kit	Code <u>C-K400092</u>
	Warp_RJ EVO white front kit	Code <u>C-K400091</u>
	Optics Light distribution: wide flood,Cover material: uv resistant polycarbonate	Code <u>83384</u>
	Optics Light distribution: medium flood,Cover material: uv resistant polycarbonate	Code <u>83383</u>
	Optics - Steel AISI 304L Light distribution: flood,Cover material: uv resistant polycarbonate	Code <u>83382</u>
	Anti-glare Anti-glare Type: honeycomb louvre. Material:Pom-C, colour:Black.	Code <u>83379</u>



Vos_RJ EVO | Downlights | Accessories
C00641BBAFL



Outer casing
 installation position: ceiling; type of installation: masonry L=370mm, H=120mm, D=200mm.
 Material:polypropylene, colour:white.

Code
89374



Outer casing
 installation position: ceiling; type of installation: masonry L=200mm, H=113mm, D=137mm.
 Material:polypropylene, colour:white.

Code
89373



Diffuser
 Diffuser Type: aesthetic filter

Code
83381



Diffuser
 Diffuser Type: elliptical filter

Code
83380



Outer casing
 installation position: ceiling; type of installation: drywall L=109mm, H=12mm, D=109mm.
 Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.

Finish
 Code
83065