





Projectors | 198-264 V AC /200-300 V DC | 1 arrayLED 18 W DC - 21 W AC | CRI 80 | Base

**C00815BBNML**


Single emission projectors for outdoor application. The natural white LED light source with a medium flood light distribution is composed of 1 arrayed LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 2996 lm, with a 166.4 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a black finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP66; the total weight is of 1.9 kg.

The total absorbed power is 21 W. The power supply cable is included and features a 1 m length.

The device features protection class II and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.29 0.29	E(0°) 20134 E(C90) 16.4° 8915 E(C0) 16.2° 8994
1.0	0.59 0.58	E(0°) 5034 E(C90) 16.4° 2229 E(C0) 16.2° 2248
1.5	0.88 0.87	E(0°) 2237 E(C90) 16.4° 991 E(C0) 16.2° 999
2.0	1.18 1.16	E(0°) 1258 E(C90) 16.4° 557 E(C0) 16.2° 562
2.5	1.47 1.45	E(0°) 805 E(C90) 16.4° 357 E(C0) 16.2° 360
3.0	1.77 1.74	E(0°) 559 E(C90) 16.4° 248 E(C0) 16.2° 250

Distance [m] Cone diameter [m] illuminance [lx]

— C0/C180 (Half-peak divergence: 32.4°)  
— C90/C270 (Half-peak divergence: 32.8°)

### Energy efficiency class

This product contains a light source of energy efficiency class E.

### Illuminotechnical Features

Light Output Ratio (LOR)	52 %
Source lumens	2996 lm
Delivered lumens	1571 lm
Consumption	21 W
Luminaire efficacy	74 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

### LED Life / Failure Ratio


L70 B10 C0 252000h (at Tj 65 Ta 25 )

### UGR

UGR axial	5.8
UGR transversal	6
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C0/C180 optics	32°
Light distribution simmetry	Symmetrical




Picket  
installation position: land,Cover material: pc

**Code**  
98549




Bag / Fixing kit - Belt for installation on tree

**Code**  
99802



Anti-glare  
Anti-glare Type: eyelid.  
Material:AISI 304 steel, colour:Black, processing:Powder coating.

**Code**  
C-U300024



Anti-glare  
Anti-glare Type: snoot.  
Material:Aluminium 6060, colour:Black, processing:Open pore anodizing + Powder Coating.

**Code**  
C-U300027