

Projectors | 176-264 V AC /176-280 V DC 1 arrayLED 10 W DC - 12 W AC | CRI 90

### C01000WHNSP





Technical data	
Туре	Track
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Spot
Light emission direction	frontal
Nominal power	10 W DC
Total Power	12 W
Source lumens	1920 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	176 - 264 V AC
Frequency	50 - 60 Hz
CCT / Tone	4000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI-2 - PUSH DIM
Directional	Swivelling
total angle (vertical plane)	90 °
total angle (horizontal plane)	360 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	0.412 Kg
Electrostatic discharge protection	Yes




















Finishing casing	9
Material	Die-cast Aluminium EN AB - 46100
Colour	White
Processing	Powder coating

The driver contained in the device complies with IEC 61347-2-13 annex J, and can therefore be powered by centralized power systems.

2 KV

Surge protection



#### Projectors | 176-264 V AC /176-280 V DC | 1 array LED 10 W DC - 12 W AC | CRI 90 | Base ${\bf C01000WHNSP}$


Single emission projectors for indoor application. The natural white LED light source with a spot light distribution is composed of 1 arrayled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 1920 lm, with a 192.0 lm/W nominal luminous efficacy.


The device body is made of die-cast aluminium en ab - 46100 and features a white finish, processed by means of powder coating. The ingress protection degree is IP20; the total weight is of 0.412 kg.

The total absorbed power is 12 W.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





#### Energy efficiency class

This product contains a light source of energy efficiency class E.

Illuminotechnical Features	
Light Output Ratio (LOR)	71 %
Source lumens	1920 lm
Delivered lumens	1368 lm
Consumption	12 W
Luminaire efficacy	114 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	90 Ra
Colour Rendering Index	60 R9
Black Body Locus	On
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C


#### LED Life / Failure Ratio


L70 B10 C0 252000h (at Tj 65 Ta 25)

UGR	
UGR axial	14.8
UGR transversal	14.8
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
C0/C180 optics	16°
Light distribution simmetry	Symmetrical

#### COLOR VECTOR GRAPHIC







		Optics Light distribution: adjustable,Cover material: uv resistant polycarbonate	<b>Code</b> C-U100002
		Optics Light distribution: adjustable,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate,uv resistant polycarbonate	<b>Code</b> C-U100003
		Optics  Light distribution: adjustable,Cover material: ,uv resistant polycarbonate,uv resistant polycarbonate,uv resistant polycarbonate	<b>Code</b> C-U100004
	035.5	Anti-glare - Accessory for focal kit with code 83347. Anti-glare Type: honeycomb louvre. Material:Pom-C, colour:Black.	<b>Code</b> 99841
		Anti-glare Anti-glare Type: honeycomb louvre. Material:Pom-C, colour:Black.	<b>Code</b> C-U300043
0		Diffuser Diffuser Type: elliptical filter	<b>Code</b> C-U300044
		Anti-glare Anti-glare Type: cylindrical screen. Material:Pom-C, colour:Black.	<b>Code</b> C-U300045
4		Anti-glare Anti-glare Type: 45° cylindrical screen. Material:Pom-C, colour:Black.	<b>Code</b> C-U300046



### Optus\_T V2 | Projectors | Accessories C01000WHNSP



Anti-glare

Anti-glare Type: cross louvres. Material:Pom-C, colour:Black.

Code

C-U300047





Electronic accessory - TWIL-DALI controller for devices with DALI protocol installed on three-phase track.

installation position: ceiling L=90mm, H=124mm, D=45mm. Material: ABS Plastic, colour: black.

Code

C-E700008



Optics

Light distribution: adjustable, Cover material: ,aluminium

Code

83347





Track

Length: 1000mm; Type of track: Standard.

Material: Aluminium, colour: White, processing: Coating.

**Finish** White

Code

83336





Length: 2000mm; Type of track: Standard.


Material: Aluminium, colour: White, processing: Coating.

Finish White

Code

83337





Track

Length: 3000mm; Type of track: Standard.

Material: Aluminium, colour: White, processing: Coating.

**Finish** White

Code 83338






Track

Length: 1000mm; Type of track: Standard.

Material: Aluminium, colour: Black, processing: Coating.

Finish

Code 83339



Length: 2000mm; Type of track: Standard.

Material: Aluminium, colour: Black, processing: Coating.

Finish

Code



### Optus\_T V2 | Projectors | Accessories C01000WHNSP





Track - Three-phase Recessed White DALI Track, 1 m (9000-1/W-R) Length: 1000mm; Type of track: Standard.

Material: Aluminium, colour: White, processing: Coating.

**Finish** Code White 80990





Track - Three-phase Recessed White DALI Track, 2 m (9000-2/W-R) Length: 2000mm; Type of track: Standard.

Material: Aluminium, colour: White, processing: Coating.

Finish White

Code 80991





Track

Length: 3000mm; Type of track: Standard. Material: Aluminium, colour: Black, processing: Coating. Finish

Code

83341





Track - Three-phase Recessed Grey DALI Track, 1 m (9000-1/B-R)

Length: 1000mm; Type of track: Standard.

Material: Aluminium, colour: Black, processing: Coating.

**Finish** 

Code

80993





Track - Trhee-phase Recessed White DALI Track, 3 m (9000-3/W-R)

Length: 3000mm; Type of track: Standard.

Material: Aluminium, colour: White, processing: Coating.

Finish White

Code

80992





Track - Three-phase Recessed Black DALI Track, 2 m (9000-1/B-R)

Length: 2000mm; Type of track: Standard.

Material: Aluminium, colour: Black, processing: Coating.

**Finish** 

Code

80994





Track - Three-phase Recessed Black DALI Track, 3 m (9000-3/B-R)


Length: 3000mm; Type of track: Standard.

Material: Aluminium, colour: Black, processing: Coating.

**Finish** 

Code

80995



Power supply - White Right power supply header (9001/W) Material:PC, colour:white.

Code

81033



### Optus\_T V2 | Projectors | Accessories C01000WHNSP


95 95 95 95 95 96 97 148	Power supply - Black Right power supply header (9001/B) Material:PC, colour:black.	<b>Code</b> 81034
95 8 3 2 - c 31 148	Power supply - White left power supply header (9002/W) Material:PC, colour:white.	<b>Code</b> 81036
95 8 31 148	Power supply - Black left power supply header (9002/B) Material:PC, colour:black.	<b>Code</b> 81037
O relition O personal	Junction - White power supply junction - central (9010/W) Type linear. Material:PC, colour:white.	Finish Code White 81042
0 mm 0	Junction - Black power supply junction - centrale (9010/B) Type linear. Material:PC, colour:black.	Finish Code Black 81043
**************************************	Junction - Flexible white junction (9018/W) Type flexible curve. Material:PC, colour:white.	Finish Code White 81066
25.4	Junction - Left white T junction - external (9013/W) Type linear. Material:PC, colour:white.	Finish Code White 81051
201 	Junction - Flexible black junction (9018/B) Type flexible curve.	Finish Code Black 81067

Type flexible curve.

Material:PC, colour:black.

### Optus\_T V2 | Projectors | Accessories C01000WHNSP





Junction - Black left T junction - external (9013/B)

Type linear.


Material:PC, colour:black.

Finish

Code

81052





Junction - Right black T junction - external (9014/B)

Type linear.


Material:PC, colour:black.

Finish Black

Code

81055





Junction - Right white T junction - external (9014/W)

Type linear.

Material:PC, colour:white.

Finish White

Code

81054



Closing cap - Black end cap 9004/B Material:PC, colour:black.

Code 81000





Junction - White electrical junction - internal (9003/W)

Type linear.


Material:PC, colour:white.

Finish White

Code

81039





Junction - Black electrical junction - internal (9003/B)

Type linear.

Material:PC, colour:black.

Finish

Code

81040





Junction - White L junction - internal (9011/W)

Type linear.

Material:PC, colour:white.

Finish White

Code 81045





Junction - Black L junction - internal (9011/B)

Type linear.

Material:PC, colour:black.

Finish

Code

81046



### Optus\_T V2 | Projectors | Accessories C01000WHNSP



Closing cap - White end cap 9004/W Material:PC, colour:white.

Code 80999



Junction - Black L junction - external (9012/B)

Finish

Code 81049

Type linear.

Material:PC, colour:black.





Junction - White L junction - external (9012/W)

Type linear.

Material:PC, colour:white.

Finish

Code

White 81048





Junction - Black X junction (9017/B)

Type linear.

Material:PC, colour:black.

Finish

Code

81064





Junction - White X junction (9017/W)

Type linear.


Material:PC, colour:white.

Finish White

Code

81063






Junction - Left white T junction - internal (9015/W)

Type linear.

Material:PC, colour:white.

**Finish** White

Code 81057



Junction - Left black T junction - internal (9015/B)

Type linear.


Material:PC, colour:black.

Finish

Code

81058





Junction - Right White T junction - internal (9016/W)

Type linear.

Material:PC, colour:white.

**Finish** White

Code 81060

9/14 22.12.2024



	25.4 25.4 26.0 27.0 28.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 29.0 20.0 20.0 20.0 20.0 20.0 20.0 20.0 20.0 20.0 20.0 20.0 20.0	Junction - Right black T junction - internal (9016/B) Type linear. Material:PC, colour:black.	Finish Black	<b>Code</b> 81061
	8 <u>STÜCCM</u> 62 32	Closing cap - Recessed black end cap 9004-R/B Material:PC, colour:black.		<b>Code</b> 81003
		Ceiling rose - 1.5m white pendant luminaires kit + bracket (9000-KIT5-1,5-W)  Material:plastic, colour:white.		<b>Code</b> 81012
stuccal		Closing cap - Recessed white end cap 9004-R/W Material:PC, colour:white.		<b>Code</b> 81002
	9 32 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	Ceiling rose - 1.5m black pendant luminaires kit + bracket ((9000-KIT5-1,5-B)  Material:plastic, colour:black.		<b>Code</b> 81014
	2 32 2 32	Ceiling rose - 5m white pendant luminaires kit + bracket (9000-KIT5-5-W) Material:plastic, colour:white.		<b>Code</b> 81013
		Ceiling rose - 5m black pendant luminaires kit + bracket (9000-KIT5-5-B)  Material:plastic, colour:black.		<b>Code</b> 81015
		Suspensions - Black rigid suspension 1m (S-9000-P3-B) Material:plastic, colour:black.		<b>Code</b> 81022



<b>2</b> 1	Bracket - Anodized fixing bracket (S-9000/131) L=35mm, H=14mm, D=24mm. Material:Aluminium, colour:translucent.	Finish Anod. Al.	<b>Code</b> 81086
	Suspensions - White rigid suspension 1m (S-9000-P3-W) Material:plastic, colour:white.		<b>Code</b> 81021
<b>3</b> 1	Bracket - White fixing braket (S-9000/131-W) L=35mm, H=14mm, D=24mm. Material:Aluminium, colour:white, processing:Coating.	<b>Finish</b> White	<b>Code</b> 81087
<b>3</b> 1 24 40	Bracket - Black fixing braket (S-9000/131-B) L=35mm, H=14mm, D=24mm. Material:Aluminium, colour:Black, processing:Coating.	Finish Black	<b>Code</b> 81088
THE STATE OF THE S	Cable cover - White recessed cover (S-9001-R/6-W) Material:PC, colour:white.		<b>Code</b> 81069
The state of the s	Cable cover - Black recessed cover (S-9001-R/6-B) Material:PC, colour:black.		<b>Code</b> 81070
o (xx/Xxx) o	Cable cover - White cover for recessed L junction (S-9011-R/6-W) Material:PC, colour:white.		<b>Code</b> 81075
o (ITERATIO)	Cable cover Material:PC, colour:black.		<b>Code</b> 81076



- 1-3-1-1	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Cable cover - White cover for recessed X junction (S-9017-R/6-W)  Material:PC, colour:white.	<b>Code</b> 81081
	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Cable cover - Black cover for recessed X junction (S-9017-R/6-B)  Material:PC, colour:black.	<b>Code</b> 81082
P	3	White three-phase adapter (9009-4/W)	<b>Code</b> 81091
	3 135 3 197 3 197 197 197	Black trhee-phase adapter (9009-4/B)	<b>Code</b> 81093
		Tool - Cutter S-9000/T	<b>Code</b> 81005
***		Suspensions - 1.5m white pendant luminaires kit (9000-KIT3-1,5-W)  Material:plastic, colour:white.	<b>Code</b> 81006
	32. 35. 36. 37. 39. 30. 31. 32. 33. 33. 34. 35. 36. 37. 38. 38. 38. 38. 38. 38. 38. 38	Suspensions - 1.5m black pendant luminaires kit (9000-KIT3-1,5-B) Material:plastic, colour:black.	<b>Code</b> 81008
		Suspensions - 5m white pendant luminaires kit (9000-KIT3-5-W) Material:plastic, colour:white.	<b>Code</b> 81007



July 1		Suspensions - White rigid suspension clip (S-9000-P2-W)  Material:plastic, colour:white.		<b>Code</b> 81018
*	33. 21 22 23 28	Suspensions - 5m black pendant luminaires kit (9000-KIT3-5-B) Material:plastic, colour:black.		<b>Code</b> 81009
		Suspensions - Black rigid suspension clip (S-9000-P2-B) Material:plastic, colour:black.		<b>Code</b> 81019
	E	Bracket - Anodized stiffening bracket (S-9000/333)  L=180mm, H=24mm, D=26mm.  Material:Aluminium, colour:Anodised Aluminum, processing:Anodisation.	Finish	<b>Code</b> 81024
	E 8 9 9 8 8	Bracket - White stiffening bracket (S-9000/333-W) L=180mm, H=24mm, D=20mm. Material:Aluminium, colour:white RAL 9010, processing:Coating.	Finish White	<b>Code</b> 81025
	ED 8	Bracket - Black stiffening bracket (S-9000/333-B) L=180mm, H=24mm, D=20mm. Material:Aluminium, colour:black RAL 9005, processing:Coating.	Finish Black	<b>Code</b> 81026
		Cable cover - Black cover for recessed junction (S-9010-R/6-B)  Material:PC, colour:black.		<b>Code</b> 81073
	+ (11171) +	Cable cover - White cover for recessed T junction (S-9013-R/6-W) Material:PC, colour:white.		<b>Code</b> 81078



0 SATURE 0	Cable cover - White cover for recessed junction (S-9010-R/6-W)  Material:PC, colour:white.	<b>Code</b> 81072
+ (1.23/1/2.21) +	Cable cover - Black cover for recessed T junction (S-9013-R/6-B)  Material:PC, colour:black.	<b>Code</b> 81079
	Cable cover  Material:black, colour:black.	<b>Code</b> 83250
	Cable cover Material:white.	<b>Code</b> 83249
3	Closing cap - White gasket (S-9001/115-W) Material:white.	<b>Code</b> 81084
3 54.0	Closing cap - Black gasket (S-9001/115-B) Material:black, colour:black.	<b>Code</b> 81085
	White three-phase/DALI adapter (9009/W)	<b>Code</b> 81094
	Black three-phase/DALI adapter (9009/B)	<b>Code</b> 81095

