




Uplights | 1 x powerLED 3 W DC 1000 mA | CRI 80  
**C01054CHMSP**



Technical data	
Type	Frame
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLED
Optics	Spot
Light emission direction	upward
Nominal power	3 W DC
Source lumens	417 lm
Input voltage range	1000mA
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP67
IK	IK05
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.180 Kg
Electrostatic discharge protection	No
Surge protection	No

### Finishing casing

Material	Brass
Colour	chrome
Processing	Electroplating

### Electronics

- C-E100034**  
 Push and Simply Dim - DALI-2 Controller (4 - 12 art.)
- C-E100033**  
 On/Off Driver 198~264V AC / 180~280V DC (4 - 12 art.)
- C-E100046**  
 On/Off Driver 100~264V AC / 176~264V DC (1 - 6 art.)
- C-E100047**  
 Push and Simply Dim - DALI-2 Controller (1 - 3 art.)



Uplights | 1 x powerLED 3 W DC 1000 mA | CRI 80 | Base  
**C01054CHMSP**

Single emission uplights for outdoor application. The super warm white LED light source with a spot light distribution is composed of 1 powered LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 417 lm, with a 139.0 lm/W nominal luminous efficacy.

The device body is made of brass and features a chrome finish, processed by means of electroplating. The ingress protection degree is IP67; the total weight is of 0.180 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 3 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 84918(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

### Energy efficiency class

This product contains a light source of energy efficiency class D.

### Illuminotechnical Features

Light Output Ratio (LOR)	64 %
Source lumens	417 lm
Delivered lumens	270 lm
Consumption	3 W
Luminaire efficacy	90 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	1.5 Step
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

### LED Life / Failure Ratio


L70 B10 C0 361980h (at Tj 60 Ta 25)

### UGR

UGR axial	13.7
UGR transversal	13.8
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

C0/C180 optics	10°
Light distribution simmetry	Symmetrical



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	0.09 0.09	E(0°) 12953 E(C90) 5.1° 6434 E(C0) 5.2° 6499
1.0	0.18 0.18	E(0°) 3238 E(C90) 5.1° 1608 E(C0) 5.2° 1625
1.5	0.27 0.27	E(0°) 1439 E(C90) 5.1° 715 E(C0) 5.2° 722
2.0	0.36 0.36	E(0°) 810 E(C90) 5.1° 402 E(C0) 5.2° 406
2.5	0.45 0.46	E(0°) 518 E(C90) 5.1° 257 E(C0) 5.2° 260
3.0	0.54 0.55	E(0°) 360 E(C90) 5.1° 179 E(C0) 5.2° 181

Distance [m] Cone diameter [m] Illuminance [lx]

— C0/C180 (Half-peak divergence: 10.4°)  
 — C90/C270 (Half-peak divergence: 10.2°)



Beret\_Q | Uplights | Accessories  
**C01054CHMSP**



Outer casing

installation position: floor, land; type of installation: masonry L=87mm, H=60mm, D=60mm.

Material:ABS Plastic, colour:black.

**Code**

84918

Springs for recessing

**Code**

LED-MOL008ACC