Gypsum_Coloring_R1 | V2



Downlights | arrayLED 0 W DC - 8 W AC | CRI 90 CA029AWHWMW








Technical data		
Туре	Encasement with flange	
Installation position	Ceiling	
Installation environment	Indoor	
Light Source	LED	
Circuit structure	arrayLED	
Optics	Medium Wide Flood	
Light emission direction	downward	
Nominal power	0 W DC	
Total Power	8 W	
Nominal input voltage	220 - 240 V AC	
Input voltage range	198 - 264 V AC	
CCT / Tone	3000 K	
Colour rendering index	90 Ra	
C.C. / C.V.	AC	
Safety class	2	
IP	IP40	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.570 Kg	
Electrostatic discharge protection	No	
Surge protection	No	





Finishing casin	g	
Material	Aluminium	
Colour	black	
Processing	Anodisation	
Finishing diffus		
Finishing diffus	ser	
Material	PMMA	
Colour	transparent	
Finishing mour		