



Uplights | 1 x powerLED 8 W DC 630 mA | RGBW - 4000
81717Q06

Single emission uplights for outdoor application. The RGBW - 4000 K LED light source with a ultra spot light distribution is composed of 1 powered LEDs with CCT of RGB-W 4000 K.

The device body is made of die-cast aluminium en ab - 46100 and features a black finish, processed by means of open pore anodizing + powder coating. The ingress protection degree is IP68; the total weight is of 0.750 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 8 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 99681 (for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Clase de eficiencia energética

Este producto contiene una fuente de luz de clase de eficiencia energética G.

Temperatura estándar del ambiente de servicio	-20 / +50°C
---	-------------

Temperatura típica sobre el vidrio	40°C
------------------------------------	------

LED Life / Failure Ratio

L70 B10 C0 202460h (at Tj 60 Ta 25)



Suelo_R RGBW | Uplights | Accessories
81717Q06




Caja de empotrar

posición de instalación: piso; tipo instalación: albañilería L=85mm, H=220mm, D=85mm.

Material:ABS, color:Negro.

Code

99681




Regulador de intensidad

RF Remote controller

Code

C-E700003



Control remoto por radiofrecuencia

Code

C-W600001