




Uplights | 198-264 V AC /--- V DC  
1 arrayLED 8 W DC - 9 W AC | CRI 80  
**82266M06**



Technical data	
Type	Drive Over
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	arrayLED
Optics	Ultra Spot
Light emission direction	upward
Nominal power	8 W DC
Total Power	9 W
Source lumens	902 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	198 - 264 V AC
Frequency	50 - 60 Hz
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP68
Installation limitations	Not for underwater use
IK	IK09
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	2000 Kg
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	2.5 Kg
Electrostatic discharge protection	Yes
Surge protection	4 KV
Product technological characteristics	Acquastop

Finishing casing	
Material	OT58 brass
Colour	Raw Brass
Finishing diffuser	
Material	Extra clear glass - Tempered
Colour	transparent
Finishing flange	
Material	OT58 brass
Colour	Raw Brass



Uplights | 198-264 V AC /--- V DC | 1 arrayLED 8 W DC - 9 W AC | CRI 80 | Base  
82266M06


Single emission uplights for outdoor application. The super warm white LED light source with a ultra spot light distribution is composed of 1 arrayed LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 902 lm, with a 112.8 lm/W nominal luminous efficacy.

The device body is made of ot58 brass and features a raw brass finish; the diffuser is made of extra clear glass - tempered. The ingress protection degree is IP68; the total weight is of 2.5 kg.

The total absorbed power is 9 W. The power supply cable is included and features a 1 m length.

The device features protection class I and can be floor-mounted with an outer casing, code 84900(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	Beam diameter [m]	E(0°)	E(C0)	6.0°
0.5	0.11	0.11	30091	14904	6.0°
1.0	0.21	0.21	7523	3726	6.0°
1.5	0.32	0.32	3343	1656	6.0°
2.0	0.42	0.42	1881	931	6.0°
2.5	0.53	0.53	1204	596	6.0°
3.0	0.63	0.63	836	414	6.0°

Distance [m] Cone diameter [m] Illuminance [lx]

— C0/C180 (Half-peak divergence: 12.0°)

## Energy efficiency class

This product contains a light source of energy efficiency class F.

## Illuminotechnical Features

Light Output Ratio (LOR)	55 %
Source lumens	902 lm
Delivered lumens	498 lm
Consumption	9 W
Luminaire efficacy	55 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	80 Ra
Black Body Locus	On
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

## LED Life / Failure Ratio

L70 B10 C0 252000h (at Tj 65 Ta 25 )

## UGR

UGR axial	10.6
UGR transversal	10.4
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

## OPTICAL

C0/C180 optics	12°
Light distribution simmetry	Symmetrical





Suelo\_Brass | Uplights | Accessories  
**82266M06**



Outer casing

installation position: floor, land; type of installation: masonry L=220mm, H=110mm,  
D=110mm.

Material:ABS Plastic, colour:black.

**Code**

84900