



# Astropek\_1 Blade V2



Uplights | 1 x powerLEDs 2 W DC 630 mA | CRI 92  
**83524W12**

Single emission uplights for outdoor application. The warm white LED light source with a radial mono-directional emission light distribution is composed of 1 powerled LEDs with CCT of 3000 K and a CRI 92; the source luminous flux is 284 lm, with a 142.0 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a grey ral 9006 finish, processed by means of coating; the diffuser is made of glass with a sandblasting treatment. The ingress protection degree is IP67; the total weight is of 0.85 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2 W. The power supply cable is included and features a 3 m length.

The device features protection class III and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

## Classe d'efficacité énergétique

Ce produit contient une source lumineuse de classe d'efficacité énergétique D.

## Caractéristiques Techniques de l'éclairage

Light Output Ratio (LOR)	19 %
Flux lumineux (source)	284 lm
Flux lumineux du luminaire	54 lm
Consumption	2,0 W
Efficacité lumineuse du luminaire	27 lm/W
Température de couleur	3000 K
Standards de Concordance de Couleur	1.5 Step
Indice de rendu chromatique	92 Ra

Température standard de l'environnement de	-20 / +50°C
Température typique sur le verre	50°C

## LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25 )

## OPTICAL

Optique C0/C180	180°
Light distribution symmetry	Symmetrical

