





## Аплайты | 1 arrayLED 9 W DC 24 V | CRI 80 82524N15

Single emission uplights for outdoor application. The natural white LED light source with a spot light distribution is composed of 1 arrayed LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 1354 lm, with a 150.4 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a black finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP68; the total weight is of 0.5 kg.

The total absorbed power is 9 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 99651 (for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.13 0.13	E(0°) 31961 E(C90) 7.4° 15772 E(C0) 7.5° 15577
1.0	0.26 0.26	E(0°) 7990 E(C90) 7.4° 3943 E(C0) 7.5° 3894
1.5	0.39 0.39	E(0°) 3551 E(C90) 7.4° 1752 E(C0) 7.5° 1731
2.0	0.52 0.53	E(0°) 1998 E(C90) 7.4° 986 E(C0) 7.5° 974
2.5	0.65 0.66	E(0°) 1278 E(C90) 7.4° 631 E(C0) 7.5° 623
3.0	0.78 0.79	E(0°) 888 E(C90) 7.4° 438 E(C0) 7.5° 433

### Класс энергоэффективности

Этот продукт содержит источник света класса энергоэффективности E .

### Лuminotechnical Особенности

Light Output Ratio (LOR)	75 %
Световой поток (источник)	1354 lm
Световой поток светильника	1018 lm
Consumption	9 W
КПД светильника	113 lm/W
Температура цвета	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Коэффициент цветопередачи	80 Ra
Стандартная температура рабочей среды	-20 / +50°C
Обычная температура стекла	40°C

### LED Life / Failure Ratio


L70 B10 C0 252000h (at Tj 65 Ta 25 )

### UGR

UGR axial	13.4
UGR transversal	13.5
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL

Оптика C0/C180	15°
Light distribution simmetry	Symmetrical



Монтажный корпус

Место установки: Пол; Тип установки: Стена из кладки L=114mm, H=76mm, D=114mm.

Материал: АБС-пластик, Цвет: черный.

**Code**

99651