



Аплайты | 1 arrayLED 9 W DC 24 V | CRI 80  
82935N30

Single emission uplights for outdoor application. The natural white LED light source with a flood light distribution is composed of 1 arrayed LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 1313 lm, with a 145.9 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a black finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP68; the total weight is of 0.5 kg.

The total absorbed power is 9 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 99651 (for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.24 0.24	E(0°) 12543 E(C90) 5789 E(C0) 5779
1.0	0.48 0.48	E(0°) 3136 E(C90) 1447 E(C0) 1445
1.5	0.72 0.73	E(0°) 1394 E(C90) 643 E(C0) 642
2.0	0.96 0.97	E(0°) 784 E(C90) 362 E(C0) 361
2.5	1.20 1.21	E(0°) 502 E(C90) 232 E(C0) 231
3.0	1.44 1.45	E(0°) 348 E(C90) 161 E(C0) 161

— C0/C180 (Half-peak divergence: 27.2°)  
— C90/C270 (Half-peak divergence: 27.0°)

### Класс энергоэффективности

Этот продукт содержит источник света класса энергоэффективности E.

### Иlluminotechnical Особенности

Light Output Ratio (LOR)	57 %
Световой поток (источник)	1313 lm
Световой поток светильника	757 lm
Consumption	9 W
КПД светильника	84 lm/W
Температура цвета	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Коэффициент цветопередачи	80 Ra
Black Body Locus	On
Стандартная температура рабочей среды	-20 / +50°C
Обычная температура стекла	40°C

### LED Life / Failure Ratio

L70 B10 C0 252000h (at Tj 65 Ta 25)

### UGR

UGR axial	10.8
UGR transversal	10.6
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

### OPTICAL


Оптика C0/C180	27°
Light distribution symmetry	Symmetrical

### COLOR VECTOR GRAPHIC





Orma\_IJ | Uplights | Accessories  
**82935N30**



Монтажный корпус

Место установки: Пол; Тип установки: Стена из кладки L=114mm, H=76mm, D=114mm.

Материал: АБС-пластик, Цвет: черный.

**Code**

99651