



# Astropek\_2 Blade V2



Аплайты | 2 x powerLEDs 4 W DC 630 mA | CRI 92  
83522N12

Double emission uplights for outdoor application. The natural white LED light source with a radial bi-directional emission light distribution is composed of 2 powered LEDs with CCT of 4000 K and a CRI 92; the source luminous flux is 606 lm, with a 151.5 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a grey ral 9006 finish, processed by means of coating; the diffuser is made of glass with a sandblasting treatment. The ingress protection degree is IP67; the total weight is of 0.85 kg.

The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 4 W. The power supply cable is included and features a 3 m length.

The device features protection class III and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

## Класс энергоэффективности

Этот продукт содержит 2 источника света класса энергоэффективности D .

## Phototechnical Особенности

Light Output Ratio (LOR)	18 %
Световой поток (источник)	606 lm
Световой поток светильника	115 lm
Consumption	4 W
КПД светильника	28 lm/W
Температура цвета	4000 K
Standard Deviation of Colour Matching	1.5 Step MacAdam
Коэффициент цветопередачи	92 Ra

Стандартная температура рабочей среды -20 / +50°C

Обычная температура стекла 50°C

## LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25 )

## OPTICAL

Оптика C0/C180	180°
Light distribution symmetry	Symmetrical

