



Подводные светильники | 3 x powerLEDs 13 W DC 350 mA | RGBW - 3000
84034V25

Single emission submerged for outdoor application. The RGBW - 3000 K LED light source with a elliptic medium flood light distribution is composed of 3 powered LEDs with CCT of RGB-W 3000 K.

The device body is made of aisi 316l steel and features a steel finish; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP68; the total weight is of 0.68 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 13 W. The power supply cable is included and features a 5 m length.


The device features protection class III and can be wall lights or floor-mounted with an outer casing, code 83141(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Стандартная температура рабочей среды	-20 / +50°C
Обычная температура стекла	40°C




Nautilus_RF | Submerged | Accessories
84034V25




Монтажный корпус - Корпус IP68 для установки на кирпичной кладке (плитка или мозаика)
Место установки: Стена; Тип установки: Стена из кладки L=131mm, H=131mm, D=139mm.
Материал: АБС-пластик, Цвет: черный.

Code
83141



Регулятор яркости
RF Remote controller

Code
C-E700003



Remote RF

Code
C-W600001