



Luminaire
 Code C00010BGARD
 Name Buzzer Pro Bollards 6.5W DC Kit Relamping
Measurem.
 Code RF_221109_03_5+
 Name Buzzer Pro Bollards 6.5W DC Kit Relamping

Luminaire Flux	129 lm	Luminaire Power	8.5 W	Efficacy	15.229 lm/W	Efficiency	100.00%
Source Flux	129 lm	Maximum value	221.67 cd/klm	Position	C=0.00 G=47.50	CG	Asymmetrical

US ROAD STANDARDS

% Lamp lm



Luminaire Classification System (LCS)				
LCS Zone	Angle	Lumens	%Lamp	%Lum
FL	0° -- 30°	7.9 lm	6.1 %	6.1 %
FM	30° -- 60°	31.0 lm	24.0 %	24.0 %
FH	60° -- 80°	20.8 lm	16.1 %	16.1 %
FVH	80° -- 90°	5.0 lm	3.9 %	3.9 %
BL	0° -- 30°	7.9 lm	6.1 %	6.1 %
BM	30° -- 60°	31.0 lm	23.9 %	23.9 %
BH	60° -- 80°	20.8 lm	16.0 %	16.0 %
BVH	80° -- 90°	5.0 lm	3.9 %	3.9 %
UL	90° -- 100°	0.0 lm	0.0 %	0.0 %
UH	100° -- 180°	0.0 lm	0.0 %	0.0 %
TOTALS		129.5 lm	100.0 %	100.0 %

BUG B0 U0 G0 Type V Short Quadrilateral Symmetry